

RSA/RSM & GSA/GSM ELECTRIC ROD-STYLE ACTUATORS

ENDURANCE TECHNOLOGY™




LINEAR SOLUTIONS MADE EASY






RSA & GSA Electric Rod-Style Actuators

WHAT ARE THE RSA & THE GSA?

The RSA is a flexible electric screw driven rod-style actuator. The standard (ST) model comes in six sizes. The guided RSA (GSA) adds guidance and load support to the design and is available in the 4 smaller sizes. The high force (HT) model is available in the 4 larger sizes, it incorporates stronger torque transmission components (couplers, pulleys, belts) and higher thrust bearings.







TOLOMATIC'S ELECTRIC ROD-STYLE ACTUATORS

	ERD	ICR	RSA	GSA	IMA
					
	Rod-Style Actuator	Integrated Control Rod-Style Actuator	Rod-Style Actuator	Guided Rod-Style Actuator	Integrated Motor Rod-Style Actuator
Thrust up to:	7,868 lbf [34,999 N]	720 lbf [3,202.7 N]	13,039 lbf [58,001 N]	950 lbf [4,226 N]	6,875 lbf [30,594 N]
Speed up to:	58 in/sec [1473 mm/sec]	25 in/sec [635 mm/sec]	123 in/sec [3,124 mm/sec]	123 in/sec [3,124 mm/sec]	52.5 in/sec [1,334 mm/sec]
Stroke Length up to:	39.4 in [1000 mm]	24 in [609 mm]	60 in [1,524 mm]	36 in [914 mm]	18 in [457 mm]
Screw/Nut Type	Solid, Ball & Roller	Ball	Solid, Ball & Roller	Solid & Ball	Ball & Roller
	<i>For complete information see www.tolomatic.com or literature number:</i>				
Literature Number:	2190-4000	2100-4000	3600-4609	3600-4609	2700-4000

(Not all models deliver maximum values listed, i.e.: Maximum thrust may not be available with maximum speed)

RSA & GSA Electric Rod-Style Actuators

Applications



Other Applications:

- Animation
- Assembly machinery
- Automatic tool changers
- Automotive
- Clamping
- Converting
- Conveyors
- Cycle testing
- Fillers
- Formers
- Hydraulic replacement
- Laser positioning
- Machine tools
- Material handling
- Medical equipment
- Molding
- Motion simulators
- Open / close doors
- Packaging equipment
- Parts clamping
- Patient lifts
- Pick & place
- Pneumatic replacement
- Precision grinders
- Product test simulations
- Riveting / fastening / joining
- Robot manipulator arms
- Sawmill equipment
- Semiconductor
- Stage motion control
- Stamping
- Table positioning
- Tension control
- Test stands
- Tube bending
- Volumetric pumps
- Water jet control
- Wave generation
- Web guidance
- Welding
- Wire winding
- and many more

CONTENTS

What are RSA & GSA	R/GSA_2
Rod-Style Actuators	R/GSA_2
Applications	R/GSA_3
RSA ST Features	R/GSA_4
RSA HT Features	R/GSA_6
RSA Options	R/GSA_6
GSA Features	R/GSA_8
RSA ST	R/GSA_10
Specifications	R/GSA_10
Performance	R/GSA_12
Specifications	R/GSA_18
Dimensions	R/GSA_18
Option Dimensions	R/GSA_20
RSA HT	R/GSA_26
Specifications	R/GSA_26
Performance	R/GSA_28
Specifications	R/GSA_32
Dimensions	R/GSA_34
Option Dimensions	R/GSA_36
GSA	R/GSA_42
Specifications	R/GSA_42
Performance	R/GSA_46
Specifications	R/GSA_42
Guide Rod Deflection	R/GSA_50
Dimensions	R/GSA_55
Option Dimensions	R/GSA_56
SWITCHES	R/GSA_57
Appl. Data Worksheet	R/GSA_59
Selection Guidelines	R/GSA_60
Service Parts Ordering	R/GSA_61
RSA ORDERING	R/GSA_62
GSA ORDERING	R/GSA_63
Tolomatic Difference	R/GSA_64

RSA-ST ROD-STYLE ACTUATOR

ENDURANCE TECHNOLOGYSM

Endurance Technology features are designed for maximum durability to provide extended service life.

The RSA rod screw actuator is ideal for medium to high thrust applications of guided loads. The compact design and cylinder style operation make this solution ideal for applications that were historically solved with pneumatic or hydraulic power. Many mounting options are available allowing the actuator to be installed in numerous applications. Built-to-order in stroke lengths up to 60 inches with your choice of screw technology.

RSA
ST


• HIGH POSITIONAL ACCURACY •

SCREW ACCURACY

Roller Nut	± 0.0004"/ft.	± 0.0102mm/300mm
Metric Ball Nut	± 0.002"/ft.	± 0.051mm/300mm

• MULTIPLE SCREW TECHNOLOGIES YOU CAN CHOOSE:

- Solid nuts of bronze or engineered resins offer quiet performance at the lowest cost; anti-backlash available
- Ball nuts offer efficiency at a cost effective price; low-backlash available



• SCREW SUPPORT BEARING •

- Engineered resin bearing provides continuous support of screw

• INTERNAL BUMPERS •

- Bumpers protect the screw and nut assembly from damage at both ends of stroke

• THRUST TUBE •

- Steel thrust tube supports extremely high force capabilities
- Salt bath nitride treatment provides excellent corrosion resistance, surface hardness and is very resistant to adherence of potential contaminants

• THREADED ROD END •


- Provides a common interface to multiple rod end options

• ROD WIPER •

- Prevents contaminants from entering the housing for extended life of the actuator

• NOSE BEARING •

- Support the thrust tube and nut assembly through entire stroke length
- Unique nose bearing material allows for smooth operation and support of the thrust rod



YOUR MOTOR HERE

YOU CAN CHOOSE:

- Specify the device to be installed and actuator ships with proper mounting hardware
- Specify and ship your device to Tolomatic for factory installation
- Motor or gearbox supplied and installed by Tolomatic

MOTOR ORIENTATION

YOU CAN CHOOSE:

- Inline option directly couples the driving shaft and is typically a one-piece housing construction for optimum alignment and support of the motor
- Reverse-parallel option minimizes the overall length and offers a belt reduction drive with a 1:1 or 2:1 ratio

HIGH THRUST BEARING

- Unique high thrust bearing assembly design eliminates runout and isolates the linear forces for the drive shaft

BREATHER / PURGE PORTS

- Standard feature on RSA 32,50,64 size actuators

- As seen in this view, located on both the bottom and the opposite side of the actuator

• Use as **Breather Port:** allows air flow into the interior of the actuator. Prevents additional load on the motor caused by air buildup due to fast cycling of the RSA.
 Use as **Purge Port:** positive pressure with air lines and filters insure contaminants (*which could potentially shorten the actuator life*) do not enter the interior of the actuator.

LIGHTWEIGHT ALUMINUM DESIGN

- Black anodized extrusion design is optimized for rigidity and strength
- External switch channels on all sides allow easy placement of position indicating switches

INTERNAL NUT BEARINGS

- Engineered resin guide bearings provide anti-rotation of the thrust rod
- Support the thrust tube and nut assembly through entire stroke length



OPTIONS

See page 7 for a complete list of RSA options including the HT-high torque option

RSA-HT OPTION

ENDURANCE TECHNOLOGYSM

The HT option is a higher thrust option for the 24, 32, 50 and 64 sizes of the RSA family. RSA actuators with roller nuts are always HT option actuators. Use Tolomatic's online sizing software to determine if the HT Option is right for your application

STANDARD FEATURES
See page 4 for a complete list of RSA standard features

REDESIGNED LMI & RP HOUSING

- Specially designed to accommodate larger motors & gearboxes with higher torques and larger bolt circles (up to 6.5", 165mm)

DURABLE BELT MATERIAL

- High torque polyurethane timing belt with carbon tensile cords resists stretching

ENHANCED HIGH THRUST BEARING

- RSA HT actuators come with high thrust angular contact ball bearing in matched pair assembly design eliminates runout and isolates the linear forces for the drive shaft

MULTIPLE SCREW TECHNOLOGIES

YOU CAN CHOOSE:

- Bronze solid nuts offer quiet performance at the lowest cost; anti-backlash available
- Ball nuts offer efficiency at a cost effective price; low-backlash available
- Roller nuts provide the highest thrust and life ratings available (HT option)



HEAVY DUTY INTERNAL BUMPERS

- Bumpers protect the screw and nut assembly from damage at both ends of stroke

WHY CHOOSE THE HT OPTION?

- Higher strength components transfer torque from the gearhead/motor through the actuator
- Grease zerks allows convenient relubrication for extended screw service life
- Allows convenient addition of gearbox to RP (Reverse Parallel mount) actuator
- Accommodates mounting large motors with up to 165mm bolt circle pattern

YOUR MOTOR HERE (Standard Feature)•

YOU CAN CHOOSE:

- Specify the device* to be installed and actuator ships with proper mounting hardware (*keyed shaft required)
- Specify and ship your device* to Tolomatic for factory installation
- Motor or gearbox supplied and installed by Tolomatic

IP67 OPTION

- Resist water ingress 1m deep for up to 30 min

RSA
HT

OPTIONS (Available for all RSA actuators unless noted)

• **METRIC OPTION**

Provides metric tapped holes for mounting of load to rod end and of actuator to mating surfaces



• **SWITCHES**

Choose from: Reed, Solid State PNP or NPN, all available normally open or normally closed

• **IP67**

Static: special gaskets for basic protection against water and dust ingress
32,50,64 sizes only: HT actuator (LMI and RP); ST actuator (RP motor mount only)

ROD END



• **MET: External Threads**
male threads



• **CLV: Clevis Rod End**
for pivoting mount



• **SRE: Spherical Rod End**
for pivoting mount



• **ALC: Alignment Coupler Rod End**
to compensate for mounting alignment



• **XR: Rod Extension**
to separate load from the actuator

MOUNTING



• **MP2: Mounting Plates**
for surface mounting



• **FFG: Front Flange**
for mounting near rod end



• **TRR: Trunnion Mount**
for pivoting mount

Below are for RP Motor mounting only




• **FM2: Foot Mount**
for surface or end mounting



• **BFG: Rear Flange**
for mounting opposite the rod end



• **PCD: Clevis**
• **PCS: Eye Mount**
for pivoting mount




THREADED ROD END

• Provides a common interface to multiple rod end options

GREASE ZERK

- This relubrication system provides extended screw service life
- Convenient lubrication without disassembly
- Standard with all HT option RSA actuators



RSA
HT

GSA GUIDED ROD-STYLE ACTUATOR

ENDURANCE TECHNOLOGYSM

Endurance Technology features are designed for maximum durability to provide extended service life.

The GSA guided screw actuator is ideal for medium to high thrust applications. The self-contained guided rod design and cylinder slide style operation make this solution ideal for applications requiring guidance and support of the load. A robust, wide tooling plate allows easy mounting of the required end effectors for many applications. Built-to-order in stroke lengths up to 36 inches with your choice of screw technology.

MULTIPLE SCREW TECHNOLOGIES

YOU CAN CHOOSE:

- Solid nuts of bronze or engineered resins offer quiet performance at the lowest cost; anti-backlash available
- Ball nuts offer efficiency at a cost effective price; low-backlash available
- Roller nuts provide the highest thrust and life ratings available



LIGHTWEIGHT ALUMINUM DESIGN

- Black anodized bearing block provides solid structural support and multiple mounting options
- Black anodized tube extrusion design is optimized for rigidity and strength
- External switch channels on all sides allow easy placement of position indicating switches

ROD WIPER


- Prevents contaminants from entering the housing for extended life of the actuator

ANODIZED ALUMINUM THRUST TUBE

- Lightweight design directly provides thrust with minimal additional inertia
- Corrosion resistant plating provides excellent protection from many chemicals

INTEGRAL GUIDE RODS AND BEARINGS

- Hardened steel guide rods provide high rigidity and low deflection
- Four composite or linear ball bearings support the load for smooth, consistent motion
- Lubrication wick supplies lube for life of actuator
- Oversized rods available for higher load capacity
- Stainless steel shafting option available for corrosion resistance



GSA

YOUR MOTOR HERE

YOU CAN CHOOSE:

- Specify the device to be installed and actuator ships with proper mounting hardware
- Specify and ship your device to Tolomatic for factory installation
- Motor or gearbox supplied and installed by Tolomatic

MOTOR ORIENTATION
YOU CAN CHOOSE:

- Inline option directly couples the driving shafts and is typically a one-piece housing construction for optimum alignment and support of the motor
- Reverse-parallel option minimizes the overall length and offers a 1:1 or 2:1 belt ratio


SCREW SUPPORT BEARINGS

- Unique high thrust bearing assembly design eliminates runout and isolates the linear forces for the drive shaft
- Engineered resin bearing provides continuous support of screw

PRECISION MACHINED SURFACES

- Extruded bearing housing is precision machined on two surfaces for true and easily aligned linear motion
- Tooling plate is aligned and assembled to provide a precise mounting surface

OPTIONS



OVERSIZED GUIDE RODS

Available for increased load capacity or decreased deflection



STOP COLLARS

Provide a positive stop mechanism when required



CORROSION RESISTANCE

Includes 316 stainless steel guide rods and fasteners for better environmental protection



METRIC OPTION

Provides metric tapped holes for mounting of load to tooling plate and of actuator to mating surfaces

SWITCHES

Choose from: Reed, Solid State PNP or NPN, all available normally open or normally closed

GSA

RSA ST Electric Rod-Style Actuator

sizeit.tolomatic.com for fast, accurate actuator selection



ACTUATOR SIZING

SIZE: ALL

units: US standard

SPECIFICATIONS

RSA
ST

RSA SIZE	MAX. STROKE in	SCREW CODE	TPI turns/in	LEAD ACCUR- ACY in/ft	BACK- LASH † in	MAX. THRUST* lbf	DYNAMIC LOAD RATING** lbf	BASE ACTUATOR INERTIA			INERTIA PER/in OF STROKE lb-in ²	DYNAMIC TORQUE TO OVERCOME FRICTION lb-in
								In Line lb-in ²	Reverse Parallel			
									1:1 lb-in ²	2:1 lb-in ²		
12	12	SN01	1.00	0.0100	0.0070	70	NA	0.004	0.005	NA	0.002	0.63
	12	SN02	2.00	0.0060	0.0070	70	NA	0.002	0.003	NA	0.001	0.56
	12	SN05	5.00	0.0060	0.0070	70	NA	0.002	0.002	NA	0.001	0.50
	12	BZ10	10.00	0.0060	0.0080	70	NA	0.002	0.002	NA	0.001	0.50
	12	BN(L)08	8.00	0.0030	0.0150	130	260	0.002	0.002	NA	0.001	0.50
16	18	SN01	1.00	0.0100	0.0070	70	NA	0.006	0.007	NA	0.002	1.31
	18	SN02	2.00	0.0060	0.0070	70	NA	0.003	0.003	NA	0.001	1.13
	18	SN05	5.00	0.0060	0.0070	70	NA	0.002	0.002	NA	0.001	1.06
	18	BZ10	10.00	0.0060	0.0080	70	NA	0.002	0.002	NA	0.001	1.06
	18	BN(L)08	8.00	0.0030	0.0150	130	260	0.002	0.002	NA	0.001	1.00
24	24	SN02	2.00	0.0050	0.0070	200	NA	0.116	0.117	0.071	0.005	1.81
	24	SN04	4.00	0.0100	0.0070	200	NA	0.116	0.117	0.071	0.004	1.69
	24	SN08	8.00	0.0100	0.0070	200	NA	0.116	0.117	0.071	0.004	1.63
	24	BZ10	10.00	0.0060	0.0080	850	NA	0.116	0.117	0.071	0.004	1.63
	24	BN(L)05	5.00	0.0030	0.0150	825	1,411	0.116	0.117	0.071	0.004	2.19
	24	BN(L)02	2.00	0.0030	0.0150	850	1,071	0.116	0.117	0.071	0.003	2.50
32	36	SN01	1.00	0.0050	0.0070	188	NA	0.235	0.179	0.147	0.013	3.13
	36	SN02	2.00	0.0050	0.0070	300	NA	0.235	0.179	0.147	0.010	2.69
	36	BZ10	10.00	0.0060	0.0080	785	NA	0.235	0.179	0.147	0.009	3.13
	36	BN(L)02	2.00	0.0040	0.0150	534	3,364	0.235	0.179	0.147	0.010	2.44
	36	BN(L)05	5.00	0.0030	0.0150	950	1,624	0.235	0.179	0.147	0.009	2.31
	36	BNM20	1.27	0.0020	0.0050	339	2,560	0.235	0.179	0.147	0.011	5.60
50	48	SN04	4.00	0.0100	0.0070	400	NA	0.654	1.104	0.458	0.028	4.25
	48	BZ10	10.00	0.0060	0.0080	1,784	NA	0.654	1.104	0.458	0.035	4.13
	48	BN(L)01	1.00	0.0040	0.0150	758	2,300	0.654	1.104	0.458	0.035	4.13
	48	BN(L)02	2.00	0.0040	0.0150	1,517	5,355	0.654	1.104	0.458	0.029	3.63
	48	BN(L)04	4.00	0.0040	0.0150	3,034	5,159	0.654	1.104	0.458	0.028	4.25
	48	BNM05	5.08	0.0020	0.0040	2,347	4,035	0.654	1.104	0.458	0.026	7.50
	48	BNM10	2.54	0.0020	0.0040	1,926	3,372	0.654	1.104	0.458	0.026	7.50
64	60	SN04	4.00	0.0100	0.0070	500	NA	2.306	2.461	2.316	0.140	5.38
	60	BZ10	10.00	0.0060	0.0080	1,781	NA	2.306	2.461	2.316	0.139	5.44
	60	BN(L)53	0.53	0.0040	0.0150	538	5,961	2.306	2.461	2.316	0.180	7.19
	60	BN(L)02	2.00	0.0040	0.0150	2,019	11,402	2.306	2.461	2.316	0.142	5.31
	60	BN(L)04	4.00	0.0040	0.0150	4,038	6,746	2.306	2.461	2.316	0.140	5.38
	60	BNM05	5.08	0.0020	0.0040	2,033	6,714	2.306	2.461	2.316	0.170	9.40
	60	BNM10	2.54	0.0020	0.0040	2,033	7,476	2.306	2.461	2.316	0.170	9.40
	60	BNM20	1.27	0.0020	0.0050	1,282	5,528	2.306	2.461	2.316	0.170	9.40

SCREW CODE	DESCRIPTION
BN	Ball Nut
BNH	Ball Nut H-series
BNL	Low-Backlash Ball Nut
BNM	Ball Nut Metric
BZ	Bronze Nut
RN	Roller Nut
SN	Solid Nut



Contact Tolomatic for higher accuracy and lower backlash options.
† (L) for low backlash ball screws: backlash = 0.0020" (0.05 mm)

* For SN & BZ screws, maximum continuous dynamic thrust subject to Thrust x Velocity limitation.

** For RN, BN & BNL screws, dynamic load rating reflects 90% reliability for 1 million revolutions.

RSM ST Electric Rod-Style Actuator

SIZE: **ALL** units: **metric****

SPECIFICATIONS

** RSM metric actuators use the same leadscrew as the RSA inch actuators. Threaded mounting and dowel pin holes are metric.

RSM SIZE	MAX. STROKE mm	SCREW CODE	LEAD mm/rev	LEAD ACCUR- ACY mm/300mm	BACK- LASH † mm	MAX. THRUST* N	DYNAMIC LOAD RATING** N	BASE ACTUATOR INERTIA			INERTIA PER/ 25mm OF STROKE kg-m ² x 10 ⁻⁶	DYNAMIC TORQUE TO OVERCOME FRICTION N-m
								Reverse Parallel				
								In Line kg-m ² x 10 ⁻⁶	1:1 kg-m ² x 10 ⁻⁶	2:1 kg-m ² x 10 ⁻⁶		
12	305	SN01	25.40	0.25	0.18	311	NA	1.171	1.463	NA	0.585	0.071
	305	SN02	12.70	0.15	0.18	311	NA	0.585	0.878	NA	0.293	0.064
	305	SN05	5.08	0.15	0.18	311	NA	0.585	0.585	NA	0.293	0.056
	305	BZ10	2.54	0.15	0.20	311	NA	0.585	0.585	NA	0.293	0.056
	305	BN(L)08	3.18	0.08	0.38	578	1,157	0.585	0.585	NA	0.293	0.056
16	457	SN01	25.40	0.25	0.18	311	NA	1.756	2.048	NA	0.585	0.148
	457	SN02	12.70	0.15	0.18	311	NA	0.878	0.878	NA	0.293	0.127
	457	SN05	5.08	0.15	0.18	311	NA	0.585	0.585	NA	0.293	0.120
	457	BZ10	2.54	0.15	0.20	311	NA	0.585	0.585	NA	0.293	0.120
	457	BN(L)08	3.18	0.08	0.38	578	1,157	0.585	0.585	NA	0.293	0.113
24	610	SN02	12.70	0.13	0.18	890	NA	33.946	34.239	20.777	1.463	0.205
	610	SN04	6.35	0.25	0.18	890	NA	33.946	34.239	20.777	1.171	0.191
	610	SN08	3.18	0.25	0.18	890	NA	33.946	34.239	20.777	1.171	0.184
	610	BZ10	2.54	0.15	0.20	3,781	NA	33.946	34.239	20.777	1.171	0.184
	610	BN(L)05	5.08	0.08	0.38	3,670	6,275	33.946	34.239	20.777	1.171	0.247
	610	BN(L)02	12.70	0.08	0.38	3,781	4,764	33.946	34.239	20.777	0.878	0.282
32	914	SN01	25.40	0.13	0.18	836	NA	68.770	52.382	43.018	3.804	0.353
	914	SN02	12.70	0.13	0.18	1,334	NA	68.770	52.382	43.018	2.926	0.304
	914	BZ10	2.54	0.15	0.20	11,121	NA	68.770	52.382	43.018	2.634	0.353
	914	BN(L)02	12.70	0.10	0.38	11,121	14,964	68.770	52.382	43.018	2.926	0.275
	914	BN(L)05	5.08	0.08	0.38	4,226	7,226	68.770	52.382	43.018	2.634	0.261
	914	BNM20	20.00	0.05	0.13	10,516	11,388	68.770	52.382	43.018	3.219	0.633
50	1219	SN04	6.35	0.25	0.18	1,779	NA	191.386	323.073	134.029	8.194	0.480
	1219	BZ10	2.54	0.15	0.20	15,569	NA	191.386	323.073	134.029	10.242	0.466
	1219	BN(L)01	25.40	0.10	0.38	10,231	10,231	191.386	323.073	134.029	10.242	0.466
	1219	BN(L)02	12.70	0.10	0.38	18,905	23,820	191.386	323.073	134.029	8.487	0.410
	1219	BN(L)04	6.35	0.10	0.38	14,457	22,949	191.386	323.073	134.029	8.194	0.480
	1219	BNM05	5.00	0.05	0.10	10,440	17,947	191.386	323.073	134.029	7.609	0.847
	1219	BNM10	10.00	0.05	0.10	10,992	14,999	191.386	323.073	134.029	7.609	0.847
64	1524	SN04	6.35	0.25	0.18	2,224	NA	674.825	720.184	677.752	40.969	0.607
	1524	BZ10	2.54	0.15	0.20	31,138	NA	674.825	720.184	677.752	40.677	0.614
	1524	BN(L)53	47.93	0.10	0.38	15,569	26,516	674.825	720.184	677.752	52.675	0.812
	1524	BN(L)02	12.70	0.10	0.38	40,257	50,719	674.825	720.184	677.752	41.555	0.600
	1524	BN(L)04	6.35	0.10	0.38	18,905	30,010	674.825	720.184	677.752	40.969	0.607
	1524	BNM05	5.00	0.05	0.10	17,375	29,865	674.825	720.184	677.752	49.749	1.062
	1524	BNM10	10.00	0.05	0.10	24,372	33,253	674.825	720.184	677.752	49.749	1.062
	1524	BNM20	20.00	0.05	0.13	22,708	24,592	674.825	720.184	677.752	49.749	1.062

SCREW CODE	DESCRIPTION
BN	Ball Nut
BNH	Ball Nut H-series
BNL	Low-Backlash Ball Nut
BNM	Ball Nut Metric
BZ	Bronze Nut
RN	Roller Nut
SN	Solid Nut

Contact Tolomatic for higher accuracy and lower backlash options.
† (L) for low backlash ball screws: backlash = 0.0020" (0.05 mm)

* For SN & BZ screws, maximum continuous dynamic thrust subject to Thrust x Velocity limitation.

** For RN, BN & BNL screws, dynamic load rating reflects 90% reliability for 1 million revolutions.

RSA
ST

RSA ST Electric Rod-Style Actuator

sizeit.tolomatic.com for fast, accurate actuator selection




ACTUATOR SIZING


SIZE: 12,16: **CRITICAL SPEED CAPACITIES**

PERFORMANCE

RSA
ST



SIZE: 24: **CRITICAL SPEED CAPACITIES**




SCREW CODE	DESCRIPTION	SCREW CODE	DESCRIPTION
BN	Ball Nut	BZ	Bronze Nut
BNH	Ball Nut H-series	RN	Roller Nut
BNL	Low-Backlash Ball Nut	SN	Solid Nut
BNM	Ball Nut Metric		

RSA ST Electric Rod-Style Actuator


SIZE: **32: CRITICAL SPEED CAPACITIES**

PERFORMANCE

**RSA
ST**



SIZE: **50: CRITICAL SPEED CAPACITIES**



SCREW CODE	DESCRIPTION	SCREW CODE	DESCRIPTION
BN	Ball Nut	BZ	Bronze Nut
BNH	Ball Nut H-series	RN	Roller Nut
BNL	Low-Backlash Ball Nut	SN	Solid Nut
BNM	Ball Nut Metric		

RSA ST Electric Rod-Style Actuator


sizeit.tolomatic.com for fast, accurate actuator selection




ACTUATOR SIZING

SIZE: 64: CRITICAL SPEED CAPACITIES

PERFORMANCE



SIZE: 12,16: PV LIMITS (Solid Nuts)



SCREW CODE	DESCRIPTION	SCREW CODE	DESCRIPTION
BN	Ball Nut	BZ	Bronze Nut
BNH	Ball Nut H-series	RN	Roller Nut
BNL	Low-Backlash Ball Nut	SN	Solid Nut
BNM	Ball Nut Metric		

PV LIMITS


PV LIMITS: Any material which carries a sliding load is limited by heat buildup. The factors that affect heat generation rate in an application are the pressure on the nut in pounds per square inch and the surface velocity in feet per minute. The product of these factors provides a measure of the severity of an application.

$$\frac{P}{(\text{Max. Thrust Rating})} \times \frac{V}{(\text{Max. Speed Rating})} \leq 0.1$$

RSA ST Electric Rod-Style Actuator


SIZE: 24,32,50,64 (SN): PV LIMITS (Solid Nuts)

PERFORMANCE



RSA
ST

SIZE: 24,32,50,64 (BZ): PV LIMITS (Bronze Nuts)



SCREW CODE	DESCRIPTION	SCREW CODE	DESCRIPTION
BN	Ball Nut	BZ	Bronze Nut
BNH	Ball Nut H-series	RN	Roller Nut
BNL	Low-Backlash Ball Nut	SN	Solid Nut
BNM	Ball Nut Metric		

PV LIMITS

PV LIMITS: Any material which carries a sliding load is limited by heat buildup. The factors that affect heat generation rate in an application are the pressure on the nut in pounds per square inch and the surface velocity in feet per minute. The product of these factors provides a measure of the severity of an application.

$$P \times V \leq 0.1$$

$$\left(\frac{\text{Thrust}}{(\text{Max. Thrust Rating})} \right) \times \left(\frac{\text{Speed}}{(\text{Max. Speed Rating})} \right) \leq 0.1$$

RSA ST Electric Rod-Style Actuator

sizeit.tolomatic.com for fast, accurate actuator selection




ACTUATOR SIZING


BALL SCREW LIFE GRAPHS

PERFORMANCE

SIZE: 12, 16, 24, 32



SIZE: 50, 64



SCREW CODE	DESCRIPTION
BN	Ball Nut
BNH	Ball Nut H-series
BNL	Low-Backlash Ball Nut
BNM	Ball Nut Metric
BZ	Bronze Nut
RN	Roller Nut
SN	Solid Nut

NOTE: The L_{10} expected life of a ball screw linear actuator is expressed as the linear travel distance that 90% of properly maintained ball screw manufactured are expected to meet or exceed. This is not a guarantee and this graph should be used for estimation purposes only.

The underlying formula that defines this value is:

$$L_{10} = \left(\frac{C}{P_e} \right)^3 \cdot \ell =$$

L_{10} Travel life in millions of units (in or mm), where:

C = Dynamic load rating (lbf) or (N)

P_e = Equivalent load (lbf) or (N)

If load is constant across all movements then:

actual load = equivalent load

ℓ = Screw lead (in/rev) (mm/rev)

Use the "Equivalent Load" calculation below, when the load is not constant throughout the entire stroke. In cases where there is only minor variation in loading, use greatest load for life calculations.

$$P_e = \sqrt[3]{\frac{L_1(P_1)^3 + L_2(P_2)^3 + L_3(P_3)^3 + L_n(P_n)^3}{L}}$$

Where:

P_e = Equivalent load (lbf) or (N)

P_n = Each increment at different load (lbf) or (N)

L = Total distanced traveled per cycle (extend + retract stroke)
 $[L = L_1 + L_2 + L_3 + L_n]$


L_n = Each increment of stroke at different load (in) or (mm)

RSA ST Electric Rod-Style Actuator


SCREW BUCKLING LOAD

PERFORMANCE


SIZE: 12, 16, 24, 32



SIZE: 50



SIZE: 64



NOTE: Buckling load limits shown assume perfect alignment. It is recommended to use additional safety margin, particularly in high thrust applications

SCREW CODE	DESCRIPTION
BN	Ball Nut
BNH	Ball Nut H-series
BNL	Low-Backlash Ball Nut
BNM	Ball Nut Metric
BZ	Bronze Nut
RN	Roller Nut
SN	Solid Nut

RSA
ST

RSA ST Electric Rod-Style Actuator

sizeit.tolomatic.com for fast, accurate actuator selection



SIZE: ALL

SPECIFICATIONS

RSA
ST

RSA (M) SIZE		12	16	24	32	50	64		
WEIGHT	BASE MODEL	IN-LINE	lb	1.73	3.73	3.98	6.11	14.21	23.01
			kg	0.78	1.68	1.79	2.75	6.39	10.35
	REVERSE PARALLEL	lb	2.40	4.00	6.25	10.40	19.66	29.69	
		kg	1.08	1.80	2.81	4.68	8.85	13.36	
PER UNIT OF STROKE	lb/in	0.128	0.300	0.330	0.460	0.860	1.380		
	g/mm	2.3	5.3	5.8	8.1	15.2	24.4		
MOVING PARTS WEIGHT	BASE WT. BZ & SN	lb	0.11	0.19	0.75	0.97	2.62	5.01	
		kg	0.05	0.09	0.34	0.44	1.19	2.27	
	BASE WT. BN	lb	0.19	0.27	1.01	1.44	3.55	7.59	
		kg	0.09	0.12	0.46	0.65	1.61	3.44	
	PER UNIT OF STROKE	lb/in	0.04	0.06	0.14	0.15	0.33	0.45	
		g/mm	0.71	1.07	2.50	2.68	5.89	8.04	
MAX. STROKE	in	12.0	18.0	24.0	36.0	48.0	60.0		
	mm	304.8	457.2	609.6	914.4	1219.2	1524		
TEMP. RANGE*	°F	40 - 130							
	°C	4 - 54							

Gasket Kit providing ingress protection against dust and splashing water available upon request

! * Heat generated by the motor and drive should be taken into consideration as well as linear velocity and work cycle time. For applications that require operation outside of the recommended temperature range, contact Tolomatic.

LARGE FRAME MOTORS AND SMALLER SIZE ACTUATORS: Cantilevered motors need to be supported, if subjected to continuous rapid reversing duty and/or under dynamic conditions.

SIDE LOADING CONSIDERATIONS: Rod screw actuators are designed to push guided and supported loads and are not meant for applications that require substantial side loading. Please contact Tolomatic for details regarding side loading capabilities.

ST ACTUATOR DIMENSIONS



NOTE: See the following page for dimensional drawing

Size		ACME NUT BALL NUT ROLLER NUT															
		A	B	C† [4x]	D	E [2x]	F	G	H	G	H	G	H	J Ø	K	RR	SS (2)
12	in	0.906	0.391	5-40 ↓0.50	1/4-28 ↓0.75	8-32 ↓0.25	0.81	2.17	2.76	2.17	2.76	-	-	0.56	0.31	0.56	-
	mm	23.01	9.93	M3x0.5 ↓12.7	M6x1.0 ↓19	M4x0.7 ↓6.3	20.7	55.1	70.1	55.1	70.1	-	-	14.2	7.8	14.3	-
16	in	0.500	1.063	8-32 ↓0.50	5/16-24 ↓0.75	8-32 ↓0.25	1.06	2.13	2.99	2.13	2.99	-	-	0.69	0.43	0.69	-
	mm	12.70	27.00	M4x0.7 ↓12.7	M8x1.25 ↓19	M4x0.7 ↓6.3	26.9	54.2	75.9	54.2	75.9	-	-	17.5	10.9	17.5	-
24	in	0.875	1.603	10-24 ↓0.79	7/16-20 ↓1.00	1/4-20 ↓0.33	1.11	2.90	3.84	3.36	4.30	4.54	5.21	1.18	0.43	1.96	-
	mm	22.23	40.72	M5x0.8 ↓20.0	M10x1.25 ↓25.0	M6x1.0 ↓8.6	28.2	73.7	97.5	85.4	109.2	115.2	132.3	30.0	10.9	49.8	-
32	in	1.181	1.969	1/4-20 ↓0.70	7/16-20 ↓1.13	5/16-18 ↓0.47	1.43	3.87	5.05	5.05	6.23	-	-	1.25	0.50	1.29	1/16-27 NPT
	mm	30.00	50.00	M6x1.0 ↓18.0	M16x1.5 ↓26.0	M8x1.25 ↓12.0	36.3	98.4	128.3	128.3	158.2	-	-	31.8	12.7	32.8	1/16-27 NPT
50	in	1.969	3.000	5/16-18 ↓1.00	3/4-16 ↓1.50	3/8-16 ↓0.75	1.95	4.78	6.44	5.78	7.44	-	-	1.75	0.70	1.86	1/8-27 NPT
	mm	50.00	76.20	M8x1.25 ↓25.4	M20x1.5 ↓38.0	M10x1.5 ↓19.0	49.5	121.5	163.6	146.9	189.0	-	-	44.5	17.8	47.1	1/8-27 NPT
64	in	1.969	3.500	7/16-14 ↓1.50	3/4-16 ↓1.50	7/16-14 ↓0.88	2.37	6.94	8.90	8.94	10.90	-	-	2.25	0.68	2.29	1/8-27 NPT
	mm	50.00	88.90	M12x1.75 ↓38.1	M27x2.0 ↓38.0	M12x1.75 ↓22.2	60.2	176.2	226.1	227.0	276.9	-	-	57.2	17.3	58.2	1/8-27 NPT

RSA ST Electric Rod-Style Actuator

SIZE: ALL


3D CAD available at www.tolomatic.com
Always use configured CAD solid model
to determine critical dimensions



DIMENSIONS

ST ACTUATOR DIMENSIONS

RSA
ST



†NOTE: RSA64 HT (All Configurations) and RSA50 HT (Roller Nut Configuration ONLY) have 6 mounting holes, all other configurations have 4 mounting holes.

∞NOTE: YM code may change this dimension. Always use configured CAD model to determine critical dimensions

Size	Motor Frame		AA	BB	CC 1:1	CC 2:1	DD	EE	FF [2x]	ALL OTHER NUTS					ROLLER NUTS					MM∞	NN	PP
										GG	HH	JJ	KK∞	LL∞	GG	HH	JJ	KK∞	LL∞			
12	17	in	1.34	3.92	2.57	NA	1.13	0.500	8-32 √0.25	1.66	1.66	0.72	1.66	1.85	-	-	-	-	-	2.26	0.61	0.188
		mm	34.1	99.6	65.3	NA	28.6	12.70	M4x0.7 √6.3	42.1	42.1	18.3	42.0	47.0	-	-	-	-	-	57.3	15.5	4.78
	23	in	1.34	3.92	2.57	NA	1.13	0.500	8-32 √0.25	1.66	1.66	0.72	2.00	2.49	-	-	-	-	-	2.26	0.61	0.188
		mm	34.1	99.6	65.3	NA	28.6	12.70	M4x0.7 √6.3	42.1	42.1	18.3	50.8	63.2	-	-	-	-	-	57.3	15.5	4.78
16	23	in	1.34	4.04	2.64	NA	1.38	0.500	8-32 √0.25	1.66	1.66	0.72	2.25	2.49	-	-	-	-	-	2.26	0.61	0.188
		mm	34.1	102.7	67.0	NA	35.0	12.70	M4x0.7 √6.3	42.1	42.1	18.3	57.2	63.2	-	-	-	-	-	57.3	15.5	4.78
24	23	in	2.04	5.13	3.68	3.65	2.04	0.787	1/4-20 √0.31	2.28	1.66	1.42	2.35	2.55	4.25	2.25	2.25	2.35	3.28	2.50	0.55	0.315
		mm	51.8	130.2	93.4	92.6	51.8	19.98	M6x1.0 √8.6	57.9	42.2	36.0	59.7	64.8	107.8	57.2	57.2	59.7	83.3	63.5	14.0	8.00
	34	in	2.04	6.29	4.09	4.06	2.04	0.787	1/4-20 √0.31	2.87	2.00	1.42	3.75	3.28	4.25	2.00	2.25	3.75	3.28	3.79	0.55	0.315
		mm	51.8	159.8	103.9	103.2	51.8	19.98	M6x1.0 √8.6	72.8	50.7	36.0	95.3	83.3	107.8	50.7	57.2	95.3	83.3	96.3	14.0	8.00
32	23	in	2.58	5.89	4.18	4.20	2.58	0.950	5/16-18 √0.50	3.19	2.00	1.79	3.00	2.63	-	-	-	-	-	2.58	0.69	0.394
		mm	65.5	149.6	106.1	106.7	65.5	24.13	M8x1.25 √12.7	80.9	50.7	45.4	76.2	66.8	-	-	-	-	-	65.5	17.5	10.00
	34	in	2.58	7.52	5.03	5.00	2.58	0.950	5/16-18 √0.50	3.19	2.00	1.79	3.75	2.38	-	-	-	-	-	4.25	0.69	0.394
		mm	65.5	190.9	127.8	126.9	65.5	24.13	M8x1.25 √12.7	80.9	50.7	45.4	95.3	60.5	-	-	-	-	-	108.0	17.5	10.00
50	23	in	3.71	8.51	6.28	6.24	3.71	1.18	3/8-16 √0.68	3.60	2.22	2.13	3.00	3.30	-	-	-	-	-	3.69	1.36	0.500
		mm	94.2	216.2	159.6	158.5	94.1	30.0	M10x1.5 √17.5	91.3	56.3	54.0	76.2	83.8	-	-	-	-	-	93.7	34.5	12.70
	34	in	3.71	8.51	6.28	6.24	3.71	1.18	3/8-16 √0.68	3.60	2.27	2.13	3.95	3.05	-	-	-	-	-	3.69	1.36	0.500
		mm	94.2	216.2	159.6	158.5	94.1	30.0	M10x1.5 √17.5	91.3	57.5	54.0	100.2	63.5	-	-	-	-	-	93.7	34.5	12.70
	56	in	3.71	9.50	6.78	6.73	3.71	1.18	3/8-16 √0.68	3.60	2.52	2.13	5.00	4.48	-	-	-	-	-	5.58	1.36	0.500
		mm	94.2	241.3	172.1	171.1	94.1	30.0	M10x1.5 √17.5	91.3	63.9	54.0	127.0	77.4	-	-	-	-	-	141.7	34.5	12.70
64	34	in	4.73	8.84	6.72	6.82	4.58	1.97	7/16-14 √0.88	4.73	2.75	3.48	3.75	3.05	-	-	-	-	-	4.48	1.36	0.750
		mm	120.2	224.6	170.7	173.2	116.3	50.0	M12x1.75 √22.2	120.2	69.9	88.3	95.2	77.5	-	-	-	-	-	113.8	34.5	19.05
	56	in	4.73	10.05	7.21	7.12	4.58	1.97	7/16-14 √0.88	4.73	2.85	3.48	5.00	4.48	-	-	-	-	-	5.73	1.36	0.750
		mm	120.2	225.3	183.1	180.8	116.3	50.0	M12x1.75 √22.2	120.2	72.4	88.3	127.0	113.8	-	-	-	-	-	145.5	34.5	19.05



RSA ST Rod End Options

SIZE: ALL

3D CAD available at www.tolomatic.com
Always use configured CAD solid model
to determine critical dimensions





SRE SPHERICAL ROD END



Allows for slight misalignment between the load and the actuator (radial and angular). Uses an industry-standard bearing.

Size		A Ø	B	C	D	E	F	G Ø	H	J
12	in	0.750	1.312	0.10	0.375	0.281	10°	0.250	1/4-28	0.75
	mm	18.00	30.00	2.5	9.00	6.80		6.00	M6x1	12.0
16	in	0.875	1.375	0.10	0.437	0.344		0.312	5/16-24	0.75
	mm	24.00	36.00	2.5	12.00	9.00		8.00	M8x1.25	16.0
24	in	1.125	1.812	0.15	0.560	0.437		0.438	7/16-20	1.06
	mm	28.00	43.00	3.8	14.00	10.50		10.00	M10x1.25	20.0
32	in	1.125	1.812	0.15	0.560	0.437		0.437	7/16-20	1.06
	mm	42.00	64.00	4.8	21.00	15.00		16.00	M16x1.5	28.0
50	in	1.750	2.875	0.19	0.875	0.687		0.750	3/4-16	1.75
	mm	50.00	77.00	4.8	25.00	18.00		20.00	M20x1.5	33.0
64	in	1.750	2.875	0.19	0.875	0.687		0.750	3/4-16	1.75
	mm	70.00	110.00	6.4	37.00	25.00		30.00	M27x2.0	51.0

CLV CLEVIS ROD END



Used with the externally threaded rod end when the actuator has to compensate for misalignment or pivot about an axis.

Size		A Ø	B	C	D	E	F	G	H
12	in	0.250	0.250	0.50	0.50	0.25	0.812	0.10	1/4-28
	mm	6.10 / 6.07	6.01 / 6.14	12.0	12.0	9.5	24.00	2.5	M6x1.0
16	in	0.375	0.375	0.50	0.75	0.38	0.875	0.10	5/16-24
	mm	8.10 / 8.07	6.01 / 6.14	16.0	16.0	13.0	32.00	2.5	M8x1.25
24	in	0.50	0.51	0.75	1.00	0.50	1.375	0.15	7/16-20
	mm	10.0	10.0	20.0	20.0	16.0	40.00	3.8	M10x1.25
32	in	0.50	0.51	0.75	1.00	0.50	1.375	0.15	7/16-20
	mm	16.0	16.0	32.0	32.0	19.0	64.00	4.8	M16x1.5
50	in	0.75	0.75	1.00	1.50	0.75	1.750	0.19	3/4-16
	mm	20.0	20.0	40.0	40.0	25.0	80.00	4.8	M20x1.5
64	in	0.75	0.75	1.00	1.50	0.75	1.750	0.19	3/4-16
	mm	30.0	30.0	54.0	55.0	45.0	110.00	6.4	M27x2.0

KEY TO SYMBOLS


- Indicates a note of high importance
- Indicates incompatibility with option(s) or size(s)
- Make note of this item

RSA ST Rod End Options

SIZE: ALL



A|L|C ALIGNMENT COUPLER

INTERNALLY THREADED END



2 SPHERICAL MOTION,
0.0625 (1.6) RADIAL FLOAT


EXTERNALLY THREADED END




Used in combination with the externally threaded rod end to provide smooth motion and extends actuator life by preventing binding caused by angular or axial misalignment. Not available for use with clevis or trunnion mounts, as they must be rigidly mounted.

THE ALIGNMENT COUPLER COMES WITH AN INTERNAL THREAD. IF AN EXTERNAL THREAD IS PREFERRED, THE ADDITION OF THE "MET" OPTION IS REQUIRED.

If you need external thread, be sure to also order the **MET** external rod end




Size		A	B	C	D	E	F
12	in	0.16	1/4-28	0.63	1.88	0.81	0.88
	mm	—	—	—	—	—	—
16	in	0.20	5/16-24	0.63	1.88	0.81	0.88
	mm	—	—	—	—	—	—
24	in	0.25	7/16-20	0.75	2.75	1.13	1.25
	mm	6.4	M10x1.25	24.0	77.0	19.0	30.0
32	in	0.25	7/16-20	0.75	2.75	1.13	1.25
	mm	8.0	M16x1.5	32.0	106.0	30.0	42.0
50	in	0.45	3/4-16	1.13	3.44	1.50	1.75
	mm	10.0	M20x1.5	42.0	122.0	30.0	42.0
64	in	0.45	3/4-16	1.13	3.44	1.50	1.75
	mm	13.5	M27x2.0	54.0	147.0	32.0	55.0



M|E|T EXTERNALLY THREADED ROD END



An alternative to the standard internally threaded end.



Size		A	B	C	D	E Ø
12	in	0.50	1/4-28	0.10	0.315	0.42
	mm	12.7	M6x1.0	2.5	8.00	10.7
16	in	0.50	5/16-24	0.10	0.375	0.48
	mm	12.7	M8x1.25	2.5	10.00	12.2
24	in	0.87	7/16-20	0.15	0.750	0.97
	mm	22.1	M10x1.25	3.8	19.00	24.6
32	in	0.87	7/16-20	0.15	0.750	0.97
	mm	28.0	M16x1.5	4.8	19.00	24.6
50	in	1.50	3/4-16	0.19	1.250	1.48
	mm	38.1	M-20x1.5	4.8	32.00	37.6
64	in	1.50	3/4-16	0.19	1.250	1.48
	mm	38.1	M27x2	6.4	32.00	38.1

RSA ST Mounting Options

SIZE: ALL

3D CAD available at www.tolomatic.com
Always use configured CAD solid model
to determine critical dimensions





FFG FRONT FLANGE MOUNT





Used when a bottom-tapped mount is not an option or where bottom support mechanisms are

not feasible. Flange can be mounted directly to framework or a bulkhead



Size		A	B Ø	C	D	E	F	G Ø	H	J
12	in	0.500	0.157	1.500	1.12	2.00	0.31	0.56	0.25	–
	mm	12.70	4.00	38.10	28.5	50.8	7.8	14.0	6.3	–
16	in	0.945	0.18	1.896	1.38	2.39	0.43	0.68	0.37	–
	mm	24.00	4.5	48.16	35.1	60.7	11.0	17.0	9.3	–
24	in	1.430	0.31	2.750	2.00	3.37	0.43	1.18	0.37	–
	mm	32.00	7.2	64.00	47.0	80.0	11.0	30.0	10.0	–
32	in	1.840	0.37	3.375	2.50	4.12	0.50	1.25	0.37	–
	mm	45.00	92.0	90.00	65.0	113.0	12.7	40.0	12.0	–
50	in	2.760	0.43	4.687	3.75	5.50	0.70	1.75	0.62	–
	mm	63.00	12.2	126.00	97.0	153.0	17.7	50.0	16.0	–
64	in	3.320	0.43	5.437	4.50	6.25	0.68	2.25	0.62	–
	mm	75.00	14.2	150.00	111.0	186.0	17.3	65.0	16.0	–

M P 2 MOUNTING PLATE



Used for mountings other than flush.

Size		A	B	C	D	E Ø
12	in	0.50	2.25	1.75	0.40	0.19
17 FRAME	mm	12.7	57.2	44.4	10.2	4.8
12 23 FRAME or YMH option	in	0.63	2.50	2.00	0.40	0.19
	mm	16.0	63.5	50.8	10.2	4.8
16	in	0.63	2.50	2.00	0.40	0.19
	mm	16.0	63.5	50.8	10.2	4.8
24	in	0.50	3.50	2.75	1.50	0.44
	mm	12.0	78.0	62.0	25.4	6.7
32	in	0.50	4.00	3.25	1.50	0.44
	mm	12.0	104.0	84.0	31.80	8.70
50	in	0.75	5.75	4.75	1.75	0.56
	mm	20.0	146.1	120.7	44.5	14.2
64	in	0.75	6.50	5.50	1.75	0.56
	mm	20.0	180.0	150.0	57.2	12.8

KEY TO SYMBOLS

- Indicates a note of high importance
- Indicates incompatibility with option(s) or size(s)
- Make note of this item

RSA ST Mounting Options

SIZE: ALL


T R R TRUNNION MOUNT




Used where space is limited in the rear of the actuator and when pivoting about an axis is required.

⊗ Not available with 12 or 16 size LMI (inline) motor mounting


RSA US standard
(Sizes: 24, 32, 50, 64)



RSM Metric
(+RSA12, RSA16)



Both RSA US standard
RSM Metric




RSA
ST

RSA: US standard	Size	A	B	C Ø	D Ø	E	F (LMI)			F (RP)		
							ACME NUT	BALL NUT	ROLLER NUT	ACME NUT	BALL NUT	ROLLER NUT
	12 in	0.38	2.25	0.4374/0.4368	0.562	0.078	NA	NA	NA	3.09	3.09	NA
	16 in	0.38	2.25	0.4374/0.4368	0.562	0.078	NA	NA	NA	3.30	3.30	NA
	24 in	1.04	4.12	0.9999/0.9993	NA	NA	4.46	4.94	6.33	4.30	4.73	6.33
	32 in	1.00	4.58	0.9999/0.9993	NA	NA	6.06	7.24	7.42	5.65	6.83	7.42
	50 in	1.06	5.83	0.9999/0.9993	NA	NA	7.44	8.44	NA	7.14	8.14	NA
	64 in	1.06	6.70	0.9999/0.9993	NA	NA	9.90	11.90	NA	9.80	11.80	NA

RSM: Metric	Size	A	B	C Ø	D Ø	E	F (LMI)			F (RP)		
							ACME NUT	BALL NUT	ROLLER NUT	ACME NUT	BALL NUT	ROLLER NUT
	12 mm	9.5	57.2	12.000/11.981	14.2	2.0	NA	NA	NA	78.5	78.5	NA
	16 mm	9.5	57.2	12.000/11.980	14.2	2.0	NA	NA	NA	83.8	83.8	NA
	24 mm	8.6	75.7	11.999/11.981	18.0	3.3	113.4	125.5	160.8	109.1	120.2	160.8
	32 mm	16.0	107.0	15.999/15.981	25.0	4.74	153.8	183.8	188.5	143.5	173.5	188.5
	50 mm	20.1	150.1	19.99/19.96	30.0	7.9	191.0	214.4	NA	181.3	206.7	NA
	64 mm	24.9	181.9	24.999/24.981	40.0	7.9	251.6	302.4	NA	248.9	299.7	NA

B F G BACK FLANGE MOUNT



Used when a bottom-tapped mount is not an option or where bottom support mechanisms are not feasible. Flange can be mounted directly to framework or a bulkhead

⊗ Not available with LMI (inline) motor mounting

Size		A	B Ø	C	D	E	F	G
12	in	0.500	0.157	1.500	1.12	2.00	0.31	–
	mm	12.70	4.00	38.10	28.5	50.8	7.8	–
16	in	0.945	0.18	1.896	1.38	2.39	0.43	–
	mm	24.00	4.5	48.16	35.1	60.7	11.0	–
24	in	1.430	0.31	2.750	2.00	3.37	0.43	–
	mm	32.00	7.2	64.00	47.0	80.0	11.0	–
32	in	1.840	0.37	3.375	2.50	4.12	0.50	–
	mm	45.00	92.0	90.00	65.0	113.0	12.7	–
50	in	2.760	0.43	4.687	3.75	5.50	0.70	–
	mm	63.00	12.2	126.00	97.0	153.0	17.7	–
64	in	3.320	0.43	5.437	4.50	6.25	0.68	–
	mm	75.00	14.2	150.00	111.0	186.0	17.3	–

RSA ST Mounting Options

SIZE: ALL

3D CAD available at www.tolomatic.com
Always use configured CAD solid model
to determine critical dimensions



P C S EYE MOUNT & P C D CLEVIS MOUNT




Used when the actuator has to compensate for misalignment or pivot about an axis when free movement is available in the back of the actuator.

⊗ Not available with LMI (inline) motor mounting



Used when the actuator has to compensate for misalignment or pivot about an axis when free movement is available in the back of the actuator.

⊗ Not available with LMI (inline) motor mounting.



Size		A	B	C Ø	D	E	F	G
12	in	0.750	0.500	0.3761 / 0.3751	0.75	1.34	0.447 / 0.442	0.453 / 0.448
	mm	19.05	12.70	10.018 / 10.000	19.0	34.0	11.35 / 11.22	11.51 / 11.38
16	in	0.750	0.500	0.3761 / 0.3751	0.75	1.34	0.447 / 0.442	0.453 / 0.448
	mm	19.05	12.70	10.018 / 10.000	19.0	34.0	11.35 / 11.22	11.51 / 11.38
24	in	1.062	0.687	0.501 / 0.500	1.00	1.98	0.750 / 0.745	0.755 / 0.751
	mm	22.00	12.00	10.03 / 10.00	20.0	50.2	25.80 / 25.60	26.12 / 26.01
32	in	1.062	0.687	0.501 / 0.500	1.00	2.58	0.750 / 0.745	0.755 / 0.751
	mm	27.00	15.00	12.03 / 12.00	26.0	65.5	31.80 / 31.60	32.12 / 32.01
50	in	1.875	1.375	0.751 / 0.750	1.50	3.60	1.250 / 1.245	1.255 / 1.251
	mm	36.00	20.00	16.03 / 16.00	40.0	91.5	49.80 / 49.60	50.12 / 50.01
64	in	1.875	1.375	0.751 / 0.750	1.50	4.48	1.250 / 1.245	1.255 / 1.251
	mm	44.00	26.00	20.03 / 20.00	40.0	113.7	59.80 / 59.60	60.12 / 60.01

KEY TO SYMBOLS

- ▲ Indicates a note of high importance
- ⊗ Indicates incompatibility with option(s) or size(s)
- 📄 Make note of this item

RSA ST Mounting Options


SIZE: ALL

F M 2 FOOT MOUNTS



Used when mounting holes on bottom of actuator are not accessible.


- ⊗ Not available with LMI (inline) motor mounting
- ⊗ Not available with HT option



Size		A	B	C Ø	D	E	F	G
12	in	0.16	0.55	0.15	0.75	1.13	0.77	0.09
	mm	4.1	14.0	3.9	19.1	28.6	19.7	2.3
16	in	0.16	0.55	0.15	0.77	1.34	1.00	0.09
	mm	4.1	14.0	3.9	19.7	34.0	25.4	2.3
24	in	0.37	1.00	0.33	1.19	2.04	1.25	0.12
	mm	7.1	23.9	7.0	29.9	51.8	32.2	3.0
32	in	0.37	1.00	0.41	1.43	2.58	1.75	0.13
	mm	9.5	32.0	9.0	36.3	64.0	45.0	3.2
50	in	0.50	1.25	0.46	1.93	3.70	2.75	0.12
	mm	16.5	41.0	12.0	49.1	96.0	63.0	3.2
64	in	0.50	1.25	0.46	2.32	4.58	3.50	0.12
	mm	19.0	41.0	14.0	59.0	113.0	75.0	3.2

RSA
ST

X R OPTIONAL ROD EXTENSION



In **vertical applications only**, the thrust rod length can be extended by specifying the rod extension option. This does not increase the working stroke, only the length of the thrust rod.

NOTE: the XR dimension in the configurator string (extension + stroke) should not exceed the maximum stroke of the specified actuator. Consult Tolomatic for extensions greater than the maximum stroke length.

Maximum Stroke Length

Size		All Others	Roller Screws
12	in	12	—
	mm	305	
16	in	18	—
	mm	457	
24	in	24	18
	mm	610	457
32	in	36	18
	mm	914	457
50	in	48	18
	mm	1219	457
64	in	60	18
	mm	1524	457

RSA HT Electric Rod-Style Actuator

sizeit.tolomatic.com for fast, accurate actuator selection



ACTUATOR SIZING

SIZE: **24, 32, 50, 64** units: **US standard**

SPECIFICATIONS

RSA SIZE	MAX. STROKE in	SCREW CODE	TPI turns/in	LEAD ACCUR-ACY in/ft	BACK-LASH † in	MAX. THRUST* lbf	DYNAMIC LOAD RATING** lbf	BASE ACTUATOR INERTIA			INERTIA PER/in OF STROKE lb-in ²	DYNAMIC TORQUE TO OVERCOME FRICTION lb-in
								In Line lb-in ²	Reverse lb-in ²	Parallel lb-in ²		
24	18	RN05	5.08	0.0004	0.0012	1,700	5,577	0.709	0.188	0.115	0.004	5.30
	18	RN10	2.54	0.0004	0.0012	1,556	5,577	0.709	0.188	0.115	0.004	5.30
32	36	BZ10	10.00	0.0060	0.0080	2,500	NA	2.252	0.338	0.160	0.009	3.13
	36	BN(L)02	2.00	0.0040	0.0150	2,500	3,364	2.252	0.338	0.160	0.010	2.44
	36	BN(L)05	5.00	0.0030	0.0150	950	1,624	2.252	0.338	0.160	0.009	2.31
	36	BNM20	1.27	0.0020	0.0050	2,364	2,560	2.252	0.338	0.160	0.011	5.60
	18	RN05	5.08	0.0004	0.0012	3,878	12,761	2.692	1.751	0.784	0.011	6.20
	18	RN10	2.54	0.0004	0.0012	4,159	12,761	2.692	1.751	0.784	0.011	6.20
50	48	BZ10	10.00	0.0060	0.0080	3,500	NA	6.537	2.026	0.843	0.035	4.13
	48	BN(L)01	1.00	0.0040	0.0150	2,300	2,300	6.537	2.026	0.843	0.035	4.13
	48	BN(L)02	2.00	0.0040	0.0150	4,250	5,355	6.537	2.026	0.843	0.029	3.63
	48	BN(L)04	4.00	0.0040	0.0150	3,250	5,159	6.537	2.026	0.843	0.028	4.25
	48	BNM05	5.08	0.0020	0.0040	2,347	4,035	6.537	2.026	0.843	0.026	7.50
	48	BNM10	2.54	0.0020	0.0040	2,471	3,372	6.537	2.026	0.843	0.026	7.50
	48	BNM25	1.02	0.0040	0.0050	2,524	2,537	6.537	2.026	0.843	0.026	7.50
	18	RN05	5.08	0.0004	0.0012	7,868	16,245	7.072	9.859	4.379	0.060	8.50
	18	RN10	2.54	0.0004	0.0012	7,868	16,245	7.072	9.859	4.379	0.060	8.50
64	60	BZ10	10.00	0.0060	0.0080	7,000	NA	16.342	13.578	7.670	0.139	5.44
	60	BN(L)53	0.53	0.0040	0.0150	3,500	5,961	16.342	13.578	7.670	0.180	7.19
	60	BN(L)02	2.00	0.0040	0.0150	9,050	11,402	16.342	13.578	7.670	0.142	5.31
	60	BN(L)04	4.00	0.0040	0.0150	4,250	6,746	16.342	13.578	7.670	0.140	5.38
	60	BNM05	5.08	0.0020	0.0040	3,906	6,714	16.342	13.578	7.670	0.170	9.40
	60	BNM10	2.54	0.0020	0.0040	5,479	7,476	16.342	13.578	7.670	0.170	9.40
	60	BNM20	1.27	0.0020	0.0050	5,105	5,528	16.342	13.578	7.670	0.170	9.40
	60	BNH(L)02	2.00	0.0040	0.0020	12,900	16,253	16.342	13.578	7.670	0.140	9.40
	18	RN05	5.08	0.0004	0.0012	13,039	23,843	16.342	13.578	7.670	0.125	9.40
	18	RN10	2.54	0.0004	0.0012	11,997	23,954	16.342	13.578	7.670	0.125	9.40
	18	RN20	1.27	0.0004	0.0012	13,039	23,954	16.342	13.578	7.670	0.125	9.40

SCREW CODE	DESCRIPTION
BN	Ball Nut
BNH	Ball Nut H-series
BNL	Low-Backlash Ball Nut
BNM	Ball Nut Metric
BZ	Bronze Nut
RN	Roller Nut
SN	Solid Nut



Contact Tolomatic for higher accuracy and lower backlash options.
† (L) for low backlash ball screws: backlash = 0.0020" (0.05 mm)

* For SN & BZ screws, maximum continuous dynamic thrust subject to Thrust x Velocity limitation.

** For RN, BN & BNL screws, dynamic load rating reflects 90% reliability for 1 million revolutions.

RSM HT Electric Rod-Style Actuator

SIZE: **24, 32, 50, 64** units: **metric****

SPECIFICATIONS

** RSM metric actuators use the same leadscrew as the RSA inch actuators. Threaded mounting and dowel pin holes are metric.

RSM SIZE	MAX. STROKE mm	SCREW CODE	LEAD mm/rev	LEAD ACCUR- ACY mm/300mm	BACK- LASH † mm	MAX. THRUST* N	DYNAMIC LOAD RATING** N	BASE ACTUATOR INERTIA			INERTIA PER/in OF STROKE kg-m ² x 10 ⁻⁶	DYNAMIC TORQUE TO OVERCOME FRICTION N-m
								In Line kg-m ² x 10 ⁻⁶	Reverse Parallel			
									1:1 kg-m ² x 10 ⁻⁶	2:1 kg-m ² x 10 ⁻⁶		
24	457	RN05	5.00	0.01	0.03	7,562	24,808	207.481	55.016	33.653	1.171	0.599
	457	RN10	10.00	0.01	0.03	6,921	24,808	207.481	55.016	33.653	1.171	0.599
32	914	BZ10	2.54	0.15	0.20	11,121	NA	659.023	98.912	46.822	2.634	0.353
	914	BN(L)02	12.70	0.10	0.38	11,121	14,964	659.023	98.912	46.822	2.926	0.275
	914	BN(L)05	5.08	0.08	0.38	4,226	7,226	659.023	98.912	46.822	2.634	0.261
	914	BNM20	20.00	0.05	0.13	10,516	11,388	659.023	98.912	46.822	3.219	0.633
	457	RN05	5.00	0.01	0.03	17,250	56,764	787.784	512.411	229.429	3.219	0.701
	457	RN10	10.00	0.01	0.03	18,500	56,764	787.784	512.411	229.429	3.219	0.701
50	1219	BZ10	2.54	0.15	0.20	15,569	NA	1912.980	592.886	246.695	10.242	0.466
	1219	BN(L)01	25.40	0.10	0.38	10,231	10,231	1912.980	592.886	246.695	10.242	0.466
	1219	BN(L)02	12.70	0.10	0.38	18,905	23,820	1912.980	592.886	246.695	8.487	0.410
	1219	BN(L)04	6.35	0.10	0.38	14,457	22,949	1912.980	592.886	246.695	8.194	0.480
	1219	BNM05	5.00	0.05	0.10	10,440	17,947	1912.980	592.886	246.695	7.609	0.847
	1219	BNM10	10.00	0.05	0.10	10,992	14,999	1912.980	592.886	246.695	7.609	0.847
	1219	BNM25	25.00	0.10	0.13	11,227	11,285	1912.980	592.886	246.695	7.609	0.847
	457	RN05	5.00	0.01	0.03	34,999	72,262	2069.542	2885.127	1281.466	17.558	0.960
457	RN10	10.00	0.01	0.03	34,999	72,262	2069.542	2885.127	1281.466	17.558	0.960	
64	1524	BZ10	2.54	0.15	0.20	31,138	NA	4782.305	3973.451	2244.540	40.677	0.614
	1524	BN(L)53	47.93	0.10	0.38	15,569	26,516	4782.305	3973.451	2244.540	52.675	0.812
	1524	BN(L)02	12.70	0.10	0.38	40,257	50,719	4782.305	3973.451	2244.540	41.555	0.600
	1524	BN(L)04	6.35	0.10	0.38	18,905	30,010	4782.305	3973.451	2244.540	40.969	0.607
	1524	BNM05	5.00	0.05	0.10	17,375	29,865	4782.305	3973.451	2244.540	49.749	1.062
	1524	BNM10	10.00	0.05	0.10	24,372	33,253	4782.305	3973.451	2244.540	49.749	1.062
	1524	BNM20	20.00	0.05	0.13	22,708	24,592	4782.305	3973.451	2244.540	49.749	1.062
	1524	BNH(L)02	12.70	0.10	0.38	57,382	72,297	4782.305	3973.451	2244.540	40.969	1.062
	457	RN05	5.00	0.01	0.03	58,001	106,059	4782.305	3973.451	2244.540	36.580	1.062
	457	RN10	10.00	0.01	0.03	53,366	106,553	4782.305	3973.451	2244.540	36.580	1.062
	457	RN20	20.00	0.01	0.03	58,001	106,553	4782.305	3973.451	2244.540	36.580	1.062

SCREW CODE	DESCRIPTION
BN	Ball Nut
BNH	Ball Nut H-series
BNL	Low-Backlash Ball Nut
BNM	Ball Nut Metric
BZ	Bronze Nut
RN	Roller Nut
SN	Solid Nut

Contact Tolomatic for higher accuracy and lower backlash options.
† (L) for low backlash ball screws: backlash = 0.0020" (0.05 mm)

* For SN & BZ screws, maximum continuous dynamic thrust subject to Thrust x Velocity limitation.

** For RN, BN & BNL screws, dynamic load rating reflects 90% reliability for 1 million revolutions.

RSA
HT

RSA HT Electric Rod-Style Actuator


sizeit.tolomatic.com for fast, accurate actuator selection




ACTUATOR SIZING

SIZE: 24: CRITICAL SPEED CAPACITIES


PERFORMANCE



SIZE: 32: CRITICAL SPEED CAPACITIES



SIZE: 50: CRITICAL SPEED CAPACITIES




SCREW CODE	DESCRIPTION
BN	Ball Nut
BNH	Ball Nut H-series
BNL	Low-Backlash Ball Nut
BNM	Ball Nut Metric
BZ	Bronze Nut
RN	Roller Nut
SN	Solid Nut

RSA HT Electric Rod-Style Actuator


SIZE: **64: CRITICAL SPEED CAPACITIES**

PERFORMANCE



**RSA
HT**

SIZE: **32,50,64 (BZ): PV LIMITS (Bronze Nuts)**



SCREW CODE	DESCRIPTION	SCREW CODE	DESCRIPTION
BN	Ball Nut	BZ	Bronze Nut
BNH	Ball Nut H-series	RN	Roller Nut
BNL	Low-Backlash Ball Nut	SN	Solid Nut
BNM	Ball Nut Metric		

PV LIMITS

PV LIMITS: Any material which carries a sliding load is limited by heat buildup. The factors that affect heat generation rate in an application are the pressure on the nut in pounds per square inch and the surface velocity in feet per minute. The product of these factors provides a measure of the severity of an application.

$$P \times V \leq 0.1$$


$$\left(\frac{\text{Thrust}}{\text{(Max. Thrust Rating)}} \right) \times \left(\frac{\text{Speed}}{\text{(Max. Speed Rating)}} \right) \leq 0.1$$




BALL & ROLLER SCREW LIFE GRAPHS

PERFORMANCE

SIZE: 24, 32



SIZE: 50, 64



SCREW CODE	DESCRIPTION
BN	Ball Nut
BNH	Ball Nut H-series
BNL	Low-Backlash Ball Nut
BNM	Ball Nut Metric
BZ	Bronze Nut
RN	Roller Nut
SN	Solid Nut

NOTE: The L_{10} expected life of a ball screw linear actuator is expressed as the linear travel distance that 90% of properly maintained ball screw manufactured are expected to meet or exceed. This is not a guarantee and this graph should be used for estimation purposes only.

The underlying formula that defines this value is:

$$L_{10} = \left(\frac{C}{P_e} \right)^3 \cdot \ell =$$

L_{10} Travel life in millions of units (in or mm), where:

C = Dynamic load rating (lbf) or (N)

P_e = Equivalent load (lbf) or (N)

If load is constant across all movements then:

actual load = equivalent load

ℓ = Screw lead (in/rev) (mm/rev)

Use the "Equivalent Load" calculation below, when the load is not constant throughout the entire stroke. In cases where there is only minor variation in loading, use greatest load for life calculations.

$$P_e = \sqrt[3]{\frac{L_1(P_1)^3 + L_2(P_2)^3 + L_3(P_3)^3 + L_n(P_n)^3}{L}}$$

Where:

P_e = Equivalent load (lbf) or (N)

P_n = Each increment at different load (lbf) or (N)

L = Total distanced traveled per cycle (extend + retract stroke)
 $[L = L_1 + L_2 + L_3 + L_n]$


L_n = Each increment of stroke at different load (in) or (mm)

RSA HT Electric Rod-Style Actuator


SCREW BUCKLING LOAD

PERFORMANCE


SIZE: 24, 32



SIZE: 50



SIZE: 64



NOTE: Buckling load limits shown assume perfect alignment. It is recommended to use additional safety margin, particularly in high thrust applications

SCREW CODE	DESCRIPTION
BN	Ball Nut
BNH	Ball Nut H-series
BNL	Low-Backlash Ball Nut
BNM	Ball Nut Metric
BZ	Bronze Nut
RN	Roller Nut
SN	Solid Nut

RSA
HT

RSA HT Electric Rod-Style Actuator

sizeit.tolomatic.com for fast, accurate actuator selection



ACTUATOR SIZING

SIZE: 24, 32, 50, 64

SPECIFICATIONS

RSA (M) SIZE			24		32			50			64		
			RN	BZ	BN	RN	BZ	BN	RN	BZ	BN	RN	
WEIGHT	BASE MODEL	IN-LINE	lb	3.98	12.76	12.76	17.29	20.58	20.58	22.08	38.10	38.10	40.06
			kg	1.79	5.79	5.79	7.84	9.33	9.33	10.01	17.28	17.28	18.17
	REVERSE PARALLEL	lb	6.25	12.01	12.01	20.36	25.32	25.32	26.82	44.43	44.43	46.39	
		kg	2.81	5.45	5.45	9.17	11.40	11.40	12.08	20.15	20.15	21.04	
	PER UNIT OF STROKE	lb/in	0.330	0.460	0.460	0.473	0.860	0.860	0.950	1.380	1.380	1.325	
		g/mm	5.8	8.1	8.1	8.4	15.2	15.2	16.8	24.4	24.4	23.4	
MOVING PARTS WEIGHT	BASE WT.	lb	1.64	0.97	1.44	3.15	2.62	3.55	6.77	5.01	7.59	12.88	
		kg	0.74	0.44	0.65	1.43	1.19	1.61	3.07	2.27	3.44	5.84	
	PER UNIT OF STROKE	lb/in	0.14	0.15	0.15	0.15	0.3	0.3	0.3	0.45	0.45	0.45	
		g/mm	2.50	2.68	2.68	2.68	5.36	5.36	5.36	8.04	8.04	8.04	
MAX. STROKE	in	18.0	36.0	36.0	18.0	48.0	48.0	18.0	60.0	60.0	18.0		
	mm	457.2	914.4	914.4	457.2	1219.2	1219.2	457.2	1524	1524	457.2		
TEMP. RANGE*	°F	50-122	40 - 130			50-122	40 - 130			50-122	40 - 130		
	°C	10-50	4 - 54			10-50	4 - 54			10-50	4 - 54		

Gasket Kit providing ingress protection against dust and splashing water available upon request

⚠ * Heat generated by the motor and drive should be taken into consideration as well as linear velocity and work cycle time. For applications that require operation outside of the recommended temperature range, contact Tolomatic.

LARGE FRAME MOTORS AND SMALLER SIZE ACTUATORS: Cantilevered motors need to be supported, if subjected to continuous rapid reversing duty and/or under dynamic conditions.

SIDE LOADING CONSIDERATIONS: Rod screw actuators are designed to push guided and supported loads and are not meant for applications that require substantial side loading. Please contact Tolomatic for details regarding side loading capabilities.


RSA
HT

RSA HT Electric Rod-Style Actuator

SIZE: 24, 32, 50, 64

SPECIFICATIONS

SPEED vs THRUST, ROLLER SCREW/NUT



PEAK REGION is the maximum performance capabilities of the actuator system

CONTINUOUS DUTY REGION is defined as the RMS thrust and velocity limit that is derived from the thermal limits of the actuator system to achieve the dynamic load rating of the screw. (Example: Extend and retract under force 100% of the time with no dwells.)

CALCULATING RMS THRUST AND VELOCITY FOR CONTINUOUS DUTY

Roller screw actuator systems have two speed/thrust curves: one for continuous duty operation and another for intermittent (peak) duty. An actuator's roller screw can be selected according to the total thrust and maximum velocity indicated by the continuous duty curve. However, by calculating the root mean square (RMS) thrust based on the application duty cycle, you may be able to take advantage of the higher peak thrust available in the intermittent duty range. The RMS thrust must fall within the continuous duty region of the motor/drive and the application maximum thrust must fall under the peak thrust of the actuator. Use the following formulas when calculating the RMS thrust and velocity. When selecting a servo actuator motor, it is necessary to add a margin of safety to the thrust and velocity required to move the load.

$$T_{RMS} = \sqrt{\frac{\sum (T_i^2 \times t_i)}{\sum (t_i)}}$$

$$V_{RMS} = \sqrt{\frac{\sum (V_i^2 \times t_i)}{\sum (t_i)}}$$

Where:

T_{RMS} = RMS Thrust
 V_{RMS} = RMS Velocity
 T_i = Thrust during interval i
 V_i = Velocity during interval i
 t_i = Time interval i

LUBRICATION

RSA roller screw actuators require periodic re-lubrication to maintain optimal performance. Below are formulas to help determine lubrication interval. See parts sheets for formula definitions, complete instructions and examples.

STEP 1: $t_{BL} = 4500 \times (V_{RMS})^{-1.57}$

STEP 2: $K_T = K_{Co} \left(\frac{T_{PEAK}}{T_{MAX}} \right) - 0.15$

STEP 3: $t_L = t_{BL} \times K_T$

	RSA24		RSA32		RSA50		RSA64		
	RN05	RN10	RN05	RN10	RN05	RN10	RN05	RN10	RN20
K_{Co}	0.25	0.39	0.24	0.23	0.17	0.17	0.17	0.17	0.22

Re-lubricate with Tolomatic Grease into the grease zerk located on the rod end.

	RSA24	RSA32	RSA50	RSA64
Quantity	0.11 oz (3.0g)	0.18 oz (5.0g)	0.28 oz (8.0g)	0.35 oz (10.0g)



In some applications oil may leak from the grease zerk. In contamination sensitive applications replace grease zerk with plug.

Where:

t_{BL} = Basic Lubrication Interval (hours)
 V_{RMS} = RMS Velocity (in/sec)
 K_T = Thrust Correction Factor
 K_{Co} = Screw Static Load Factor
 T_{PEAK} = Actuator Peak Thrust Rating
 T_{MAX} = Maximum Cycle Thrust
 t_L = Lubrication Interval (hours)

**RSA
HT**

RSA HT Electric Rod-Style Actuator

SIZE: 24,32,50,64


3D CAD available at www.tolomatic.com
Always use configured CAD solid model to determine critical dimensions



HT ACTUATOR DIMENSIONS




NOTE: See page R/GSA_19 for additional dimensions




†NOTE: RSA64 HT (All Configurations) and RSA50 HT (Roller Nut Configuration ONLY) have 6 mounting holes, all other configurations have 4 mounting holes.

LM Motor Mount



RP Motor Mount



∞NOTE: YM code may change this dimension. Always use configured CAD model to determine critical dimensions

Size		A	B	C†	D	E	F	JØ	K	EE	KK [Frame Size] ∞			SS (2)
											23	34	56	
24	in	0.875	1.603	10-24 \downarrow 0.79	7/16-20 \downarrow 1.00	1/4-20 \downarrow 0.33	1.11	1.18	0.43	0.950	2.35	3.75	NA	NA
	mm	22.23	40.72	M5x0.8 \downarrow 20.0	M10x1.25 \downarrow 25.0	M6x1.0 \downarrow 8.6	28.2	30.0	10.9	19.98	59.7	95.3	NA	NA
32	in	1.181	1.969	1/4-20 \downarrow 0.70	7/16-20 \downarrow 1.13	1/4-20 \downarrow 0.33	1.43	1.25	0.50	0.950	3.00	3.75	NA	1/16-27 NPT
	mm	30.00	50.00	M6x1.0 \downarrow 18.0	M16x1.5 \downarrow 26.0	M6x1.0 \downarrow 8.6	36.3	31.8	12.7	24.13	76.2	95.3	NA	1/16-27 NPT
50	in	1.969	3.000	5/16-18 \downarrow 0.47	3/4-16 \downarrow 1.50	5/16-18 \downarrow 0.47	1.95	1.75	0.70	1.18	3.00	3.95	5.00	1/8-27 NPT
	mm	50.00	76.20	M8x1.25 \downarrow 12.0	M20x1.5 \downarrow 38.0	M8x1.25 \downarrow 12.0	49.5	49.5	17.8	30.0	76.2	100.2	127.0	1/8-27 NPT
64	in	1.969	3.500	1/2-13 \downarrow 0.75	1-1/4-12 \downarrow 2.50	7/16-14 \downarrow 0.88	2.37	2.25	0.68	1.97	NA	3.75	5.00	1/8-27 NPT
	mm	50.00	88.90	M12x1.75 \downarrow 18.0	M27x2.0 \downarrow 63.5	M12x1.75 \downarrow 22.2	60.2	57.2	17.3	50.0	NA	95.3	127.0	1/8-27 NPT

RSA HT Electric Rod-Style Actuator

SIZE: 24,32,50,64



HT ACTUATOR DIMENSIONS



NOTE: See page R/GSA_19 for additional dimensions


Drawing repeated for reference

LMI Motor Mount



†NOTE: RSA64 HT (All Configurations) and RSA50 HT (Roller Nut Configuration ONLY) have 6 mounting holes, all other configurations have 4 mounting holes.

RP Motor Mount



∞NOTE: YM code may change this dimension. Always use configured CAD model to determine critical dimensions

Size	BZ10		ROLLER NUTS																			
	G	H	G	H	L	AA	BB	CC 1:1	CC 2:1	DD	GG	HH∞	JJ	LL [Frame Size]			MM	NN	PP	RR	TT	
														23	34	56						
24	in	2.90	3.84	4.54	5.21	NA	2.04	5.13	3.68	3.65	2.04	4.25	2.25	2.25	3.28	3.28	NA	2.50	0.55	0.315	1.96	2.04
	mm	73.7	97.5	115.2	132.3	NA	5.18	130.2	93.4	92.6	51.8	107.8	57.2	57.2	83.3	83.3	NA	63.5	14.0	8.00	49.8	51.8
32	in	3.87	5.05	5.92	5.74	NA	3.25	7.88	5.56	5.55	2.58	5.83	2.33	3.50	4.14	4.10	NA	4.38	1.69	0.625	1.63	3.25
	mm	98.4	128.3	150.4	145.7	NA	82.6	200.0	141.3	140.8	65.5	148.1	59.2	88.9	105.1	104.2	NA	111.1	43.0	15.9	41.3	82.6
50	in	4.78	6.44	7.21	8.41	3.00	5.88	11.00	7.85	7.92	3.71	6.80	3.00	3.80	NA	5.21	5.41	5.88	2.30	0.730	2.83	3.71
	mm	121.5	163.6	183.1	213.6	76.2	149.2	279.4	199.3	201.1	94.2	172.7	76.2	96.5	NA	132.4	137.4	149.2	58.4	18.54	71.8	94.2
64	in	7.80	9.29	7.80	9.29	3.50	6.88	12.10	8.81	8.75	4.58	7.75	3.50	4.50	NA	5.88	5.88	6.88	1.85	0.999	3.30	4.58
	mm	198	235.9	198.0	235.9	88.9	174.6	306.1	223.9	222.3	116.3	196.9	88.9	108.0	NA	149.3	149.3	174.6	47.1	25.37	83.8	116.3

Size	BALL NUTS		ALL OTHER NUTS																	
	G	H	L	AA	BB	CC 1:1	CC 2:1	DD	GG	HH∞	JJ	LL [Frame Size]			MM	NN	PP	RR	TT	
												23	34	56						
24	in	3.36	4.30	NA	2.04	5.13	3.68	3.65	2.04	2.28	1.66	1.42	2.55	3.28	NA	2.50	0.55	0.315	1.96	2.04
	mm	85.4	109.2	NA	5.18	130.2	93.4	92.6	51.8	57.9	42.2	36.0	64.8	83.3	NA	63.5	14.0	8.00	49.8	51.8
32	in	5.05	6.23	NA	2.58	7.52	4.83	4.8	2.58	3.19	2.00	1.79	4.14	4.10	NA	4.25	1.75	0.531	1.29	2.58
	mm	128.3	158.2	NA	65.5	190.9	122.8	121.9	65.5	80.9	50.7	45.4	105.1	104.2	NA	108	44.5	13.49	32.8	65.5
50	in	5.78	7.44	NA	3.71	9.50	6.68	6.62	3.71	3.60	2.20	2.13	NA	5.36	5.41	5.58	2.30	0.730	1.85	3.71
	mm	146.9	189.0	NA	94.2	241.3	169.6	168.1	94.2	91.3	55.9	54.0	NA	136.2	137.4	141.7	58.4	18.54	47.1	94.2
64	in	10.25	11.7	3.50	6.88	12.1	8.81	8.75	4.58	7.75	3.50	4.50	NA	5.88	5.88	6.88	1.85	0.999	3.30	4.58
	mm	260.3	298.2	88.9	174.6	306.1	223.9	222.3	116.3	196.9	88.9	108.0	NA	149.3	149.3	174.6	47.1	25.37	83.8	116.3

**RSA
HT**


RSA HT Rod End Options

SIZE: 24, 32, 50, 64

3D CAD available at www.tolomatic.com
Always use configured CAD solid model
to determine critical dimensions




SRE SPHERICAL ROD END



Allows for slight misalignment between the load and the actuator (radial and angular). Uses an industry-standard bearing.

Size		A Ø	B	C	D	E	F	G Ø	H	J
24	in	1.125	1.812	0.15	0.560	0.437	10°	0.438	7/16-20	1.06
	mm	28.00	43.00	3.8	14.00	10.50		10.00	M10x1.25	20.0
32	in	1.125	1.812	0.15	0.560	0.437		0.437	7/16-20	1.06
	mm	42.00	64.00	4.8	21.00	15.00		16.00	M16x1.5	28.0
50	in	1.750	2.875	0.19	0.875	0.687		0.750	3/4-16	1.75
	mm	50.00	77.00	4.8	25.00	18.00		20.00	M20x1.5	33.0
64	in	2.750	4.125	0.19	1.375	1.000		1.00	1-1/4-12	2.13
	mm	70.00	110.00	6.4	37.00	25.00		30.00	M27x2.0	51.0

CLV CLEVIS ROD END



Used with the externally threaded rod end when the actuator has to compensate for misalignment or pivot about an axis.

Size		A Ø	B	C	D	E	F	G	H
24	in	0.50	0.51	0.75	1.00	0.50	1.375	0.15	7/16-20
	mm	10.0	10.0	20.0	20.0	16.0	40.00	3.8	M10x1.25
32	in	0.50	0.51	0.75	1.00	0.50	1.375	0.15	7/16-20
	mm	16.0	16.0	32.0	32.0	19.0	64.00	4.8	M16x1.5
50	in	0.75	0.75	1.00	1.50	0.75	1.750	0.19	3/4-16
	mm	20.0	20.0	40.0	40.0	25.0	80.00	4.8	M20x1.5
64	in	1.375	2.03	1.75	4.03	1.38	3.750	0.19	1-1/4-12
	mm	30.0	30.0	54.0	55.0	45.0	110.00	6.4	M27x2.0

KEY TO SYMBOLS


- ▲ Indicates a note of high importance
- ⊗ Indicates incompatibility with option(s) or size(s)
- 📄 Make note of this item

RSA HT Rod End Options



SIZE: 24, 32, 50, 64

A|L|C ALIGNMENT COUPLER

INTERNALLY THREADED END




EXTERNALLY THREADED END




Used in combination with the externally threaded rod end to provide smooth motion and extends actuator life by preventing binding caused by angular or axial misalignment. Not available for use with clevis or trunnion mounts, as they must be rigidly mounted.

THE ALIGNMENT COUPLER COMES WITH AN INTERNAL THREAD. IF AN EXTERNAL THREAD IS PREFERRED, THE ADDITION OF THE "MET" OPTION IS REQUIRED.

If you need external thread, be sure to also order the **MET** external rod end



Size		A	B	C	D	E	F
24	in	0.25	7/16-20	0.75	2.75	1.13	1.25
	mm	6.4	M10x1.25	24.0	77.0	19.0	30.0
32	in	0.25	7/16-20	0.75	2.75	1.13	1.25
	mm	8.0	M16x1.5	32.0	106.0	30.0	42.0
50	in	0.45	3/4-16	1.13	3.44	1.50	1.75
	mm	10.0	M20x1.5	42.0	122.0	30.0	42.0
64	in	0.50	1-1/4-12	1.63	4.56	2.25	2.50
	mm	13.5	M27x2.0	54.0	147.0	32.0	55.0




RSA
HT

M|E|T EXTERNALLY THREADED ROD END



An alternative to the standard internally threaded end.



Size		A	B	C	D	E Ø
24	in	0.87	7/16-20	0.15	0.750	0.97
	mm	22.1	M10x1.25	3.8	19.00	24.6
32	in	0.87	7/16-20	0.15	0.750	0.97
	mm	28.0	M16x1.5	4.8	19.00	24.6
50	in	1.50	3/4-16	0.19	1.250	1.48
	mm	38.1	M-20x1.5	4.8	32.00	37.6
64	in	2.13	1-1/4-12	0.19	1.313	1.60
	mm	50.8	M27x2	6.4	32.00	38.1

RSA HT Mounting Options

SIZE: 24, 32, 50, 64

3D CAD available at www.tolomatic.com
Always use configured CAD solid model
to determine critical dimensions





FFG FRONT FLANGE MOUNT



Used when a bottom-tapped mount is not an option or where bottom support mechanisms are



not feasible. Flange can be mounted directly to framework or a bulkhead



Size		A	B Ø	C	D	E	F	G Ø	H	J
24	in	1.430	0.31	2.750	2.00	3.37	0.43	1.18	0.37	–
	mm	32.00	7.2	64.00	47.0	80.0	11.0	30.0	10.0	–
32	in	1.840	0.37	3.375	2.50	4.12	0.50	1.25	0.37	–
	mm	45.00	92.0	90.00	65.0	113.0	12.7	40.0	12.0	–
50	in	2.760	0.43	4.687	3.75	5.50	1.32	1.75	0.62	–
	mm	63.00	12.2	126.00	97.0	153.0	33.5	50.0	16.0	–
50 RN	in	2.760	0.43	7.000	3.75	8.00	1.32	1.75	0.62	3.00
	mm	63.00	12.2	177.80	97.0	203.2	33.5	50.0	16.0	76.2
64	in	3.320	0.58	8.000	4.50	9.00	0.86	2.25	0.80	3.50
	mm	75.00	14.7	203.2	114.3	228.6	21.8	65.0	20.3	88.9

RSA
HT

M P 2 MOUNTING PLATE



Used for mountings other than flush.

Size		A	B	C	D	E Ø
24	in	0.50	3.50	2.75	1.50	0.44
	mm	12.0	78.0	62.0	25.4	6.7
32	in	0.50	4.00	3.25	1.50	0.44
	mm	12.0	104.0	84.0	31.80	8.70
50	in	0.75	5.75	4.75	1.75	0.56
	mm	20.0	146.1	120.7	44.5	14.2
50 RN	in	1.25	5.75	4.75	1.75	0.56
	mm	31.8	146.1	120.7	44.5	14.2
64	in	0.75	6.50	5.50	1.75	0.56
	mm	20.0	180.0	150.0	57.2	12.8
64	in	1.25	6.50	5.50	1.75	0.56
	mm	31.8	180.0	150.0	44.5	12.8

KEY TO SYMBOLS

- Indicates a note of high importance
- Indicates incompatibility with option(s) or size(s)
- Make note of this item

RSA HT Mounting Options


SIZE: 24, 32, 50, 64

T R R TRUNNION MOUNT




Used where space is limited in the rear of the actuator and when pivoting about an axis is required.

RSA US standard
(Sizes: 24, 32, 50, 64)



Both RSA US standard
RSM Metric




RSA: US standard	Size	in	A	B	C Ø	D Ø	E	F (LMI)			F (RP)		
								ACME NUT	BALL NUT	ROLLER NUT	ACME NUT	BALL NUT	ROLLER NUT
								24	1.04	4.12	0.9999/0.9993	NA	NA
32	1.00	4.58	0.9999/0.9993	NA	NA	6.06	7.24	7.42	5.65	6.83	7.42		
50	1.06	5.83	0.9999/0.9993	NA	NA	7.44	8.44	9.07	7.14	8.14	9.07		
64	1.25	7.92	0.9999/0.9993	1.50	0.42	10.29	12.74	10.29	10.29	12.74	10.29		

RSM: Metric	Size	mm	A	B	C Ø	D Ø	E	F (LMI)			F (RP)		
								ACME NUT	BALL NUT	ROLLER NUT	ACME NUT	BALL NUT	ROLLER NUT
								24	8.6	75.7	11.999/11.981	18.0	3.3
32	16.0	107.0	15.999/15.981	25.0	4.74	153.8	183.8	188.5	143.5	173.5	188.5		
50	20.1	150.1	19.99/19.96	30.0	7.9	191.0	214.4	230.3	181.3	206.7	230.3		
64	24.9	181.9	24.999/24.981	40.0	7.9	261.3	323.6	261.3	261.3	323.6	261.3		

RSA
HT

B F G BACK FLANGE MOUNT



Used when a bottom-tapped mount is not an option or where bottom support mechanisms are not feasible. Flange can be mounted directly to framework or a bulkhead

⊗ Not available with LMI (inline) motor mounting

Size		A	B Ø	C	D	E	F	G
24	in	1.430	0.31	2.750	2.00	3.37	0.43	–
	mm	32.00	7.2	64.00	47.0	80.0	11.0	–
32	in	1.840	0.37	3.375	2.50	4.12	0.50	–
	mm	45.00	92.0	90.00	65.0	113.0	12.7	–
50	in	2.760	0.43	4.687	3.75	5.50	1.32	–
	mm	63.00	12.2	126.00	97.0	153.0	33.5	–
50 RN	in	2.760	0.43	7.000	3.75	8.00	1.32	3.00
	mm	63.00	12.2	177.80	97.0	203.2	33.5	76.2
64	in	3.320	0.58	8.000	4.50	9.00	0.86	3.50
	mm	75.00	14.7	203.2	114.3	228.6	21.8	88.9

RSA HT Mounting Options

SIZE: 24, 32, 50, 64

3D CAD available at www.tolomatic.com
Always use configured CAD solid model
to determine critical dimensions



PCS EYE MOUNT & PCD CLEVIS MOUNT




Used when the actuator has to compensate for misalignment or pivot about an axis when free movement is available in the back of the actuator.

⊗ Not available with LMI (inline) motor mounting



Used when the actuator has to compensate for misalignment or pivot about an axis when free movement is available in the back of the actuator.

⊗ Not available with LMI (inline) motor mounting.



Size		A	B	C Ø	D	E	F	G
24	in	1.062	0.687	0.501 / 0.500	1.00	1.98	0.750 / 0.745	0.755 / 0.751
	mm	22.00	12.00	10.03 / 10.00	20.0	50.2	25.80 / 25.60	26.12 / 26.01
32	in	1.062	0.687	0.501 / 0.500	1.00	2.58	0.750 / 0.745	0.755 / 0.751
	mm	27.00	15.00	12.03 / 12.00	26.0	65.5	31.80 / 31.60	32.12 / 32.01
50	in	1.875	1.375	0.751 / 0.750	1.50	3.60	1.250 / 1.245	1.255 / 1.251
	mm	36.00	20.00	16.03 / 16.00	40.0	91.5	49.80 / 49.60	50.12 / 50.01
64	in	2.335	1.535	1.003 / 1.002	2.00	4.48	1.500 / 1.495	1.505 / 1.501
	mm	59.31	38.99	28.03 / 28.00	50.8	113.7	39.90 / 39.80	40.10 / 40.00

KEY TO SYMBOLS


- ▲ Indicates a note of high importance
- ⊗ Indicates incompatibility with option(s) or size(s)
- 📄 Make note of this item

RSA HT


RSA HT Mounting Options

SIZE: 24, 32, 50, 64

OPTIONAL ROD EXTENSION



In **vertical applications only**, the thrust rod length can be extended by specifying the rod extension option. This does not increase the working stroke, only the length of the thrust rod.

 **NOTE:** the XR dimension in the configurator string (extension + stroke) should not exceed the maximum stroke of the specified actuator. Consult Tolomatic for extensions greater than the maximum stroke length.

Maximum Stroke Length

Size		All Others	Roller Screws
24	in	24	18
	mm	610	457
32	in	36	18
	mm	914	457
50	in	48	18
	mm	1219	457
64	in	60	18
	mm	1524	457

**RSA
HT**

GSA Guided Electric Rod-Style Actuator

sizeit.tolomatic.com for fast, accurate actuator selection



ACTUATOR SIZING

SIZE: ALL

units: US standard

SPECIFICATIONS

GSA SIZE	BEARING TYPE	GUIDE ROD	MAX. STROKE	SCREW TYPE	TPI	LEAD ACCURACY†	BACKLASH	MAX THRUST*	DYNAMIC LOAD RATING**	BASE ACTUATOR INERTIA			INERTIA PER/in OF STROKE	DYNAMIC FRICTION TORQUE	MOVING PARTS WEIGHT		
										In Line	Reverse Parallel				Base	Per Inch	
											1:1	2:1					
in	in	in	in	turns/in	in/ft	in	lbf	lbf	lb-in ²	lb-in ²	lb-in ²	lb-in	lb	lb			
12	LINEAR	STANDARD Ø0.50	18	SN01	1	0.010	0.007	70	NA	0.004	0.005	NA	0.002	2.938	1.21	0.14	
			18	SN02	2	0.006	0.007	70	NA	0.002	0.003	NA	0.001	1.500	1.21	0.14	
			18	SN05	5	0.006	0.007	70	NA	0.002	0.002	NA	0.001	0.563	1.21	0.14	
			18	BZ10	10	0.006	0.008	70	NA	0.002	0.002	NA	0.001	0.438	1.21	0.14	
			18	BN(L)08	8	0.003	0.015	130	260	0.002	0.002	NA	0.001	0.500	1.29	0.14	
	COMPOSITE	STANDARD Ø0.50	18	SN01	1	0.010	0.007	70	NA	0.004	0.005	NA	0.002	5.625	1.21	0.14	
			18	SN02	2	0.006	0.007	70	NA	0.002	0.003	NA	0.001	2.813	1.21	0.14	
			18	SN05	5	0.006	0.007	70	NA	0.002	0.002	NA	0.001	1.125	1.21	0.14	
			18	BZ10	10	0.006	0.008	70	NA	0.002	0.002	NA	0.001	0.813	1.21	0.14	
			18	BN(L)08	8	0.003	0.015	130	260	0.002	0.002	NA	0.001	0.688	1.29	0.14	
		OVERSIZED Ø0.63	18	SN01	1	0.010	0.007	70	NA	0.004	0.005	NA	0.002	6.125	1.56	0.20	
			18	SN02	2	0.006	0.007	70	NA	0.002	0.003	NA	0.001	3.063	1.56	0.20	
			18	SN05	5	0.006	0.007	70	NA	0.002	0.002	NA	0.001	1.250	1.56	0.20	
			18	BZ10	10	0.006	0.008	70	NA	0.002	0.002	NA	0.001	0.938	1.56	0.20	
			18	BN(L)08	8	0.003	0.015	130	260	0.002	0.002	NA	0.001	0.750	1.64	0.20	
	16	LINEAR	STANDARD Ø0.63	24	SN01	1	0.010	0.007	70	NA	0.006	0.007	NA	0.002	2.938	2.42	0.21
				24	SN02	2	0.006	0.007	70	NA	0.003	0.003	NA	0.001	1.500	2.42	0.21
				24	SN05	5	0.006	0.007	70	NA	0.002	0.002	NA	0.001	0.563	2.42	0.21
24				BZ10	10	0.006	0.008	70	NA	0.002	0.002	NA	0.001	0.438	2.42	0.21	
24				BN(L)08	8	0.003	0.015	130	260	0.002	0.002	NA	0.001	0.500	2.50	0.21	
COMPOSITE		STANDARD Ø0.63	24	SN01	1	0.010	0.007	70	NA	0.006	0.007	NA	0.002	6.125	2.42	0.21	
			24	SN02	2	0.006	0.007	70	NA	0.003	0.003	NA	0.001	3.063	2.42	0.21	
			24	SN05	5	0.006	0.007	70	NA	0.002	0.002	NA	0.001	1.250	2.42	0.21	
			24	BZ10	10	0.006	0.008	70	NA	0.002	0.002	NA	0.001	0.938	2.42	0.21	
			24	BN(L)08	8	0.003	0.015	130	260	0.002	0.002	NA	0.001	0.688	2.50	0.21	
		OVERSIZED Ø0.75	24	SN01	1	0.010	0.007	70	NA	0.006	0.007	NA	0.002	6.625	2.94	0.29	
			24	SN02	2	0.006	0.007	70	NA	0.003	0.003	NA	0.001	3.313	2.94	0.29	
			24	SN05	5	0.006	0.007	70	NA	0.002	0.002	NA	0.001	1.313	2.94	0.29	
			24	BZ10	10	0.006	0.008	70	NA	0.002	0.002	NA	0.001	1.000	2.94	0.29	
			24	BN(L)08	8	0.003	0.015	130	260	0.002	0.002	NA	0.001	0.750	3.02	0.29	

SCREW CODE	DESCRIPTION
BN	Ball Nut
BNH	Ball Nut H-series
BNL	Low-Backlash Ball Nut
BNM	Ball Nut Metric

SCREW CODE	DESCRIPTION
BZ	Bronze Nut
RN	Roller Nut
SN	Solid Nut



Contact Tolomatic for higher accuracy and lower backlash options.

† (L) for low backlash ball screws: backlash = 0.0020" (0.05 mm)

* For SN & BZ screws, maximum continuous dynamic thrust subject to Thrust x Velocity limitation.

** For RN, BN & BNL screws, dynamic load rating reflects 90% reliability for 1 million revolutions.

GSA

GSA Guided Electric Rod-Style Actuator

SIZE: **ALL**

units: **US standard**

SPECIFICATIONS

GSA SIZE	BEARING TYPE	GUIDE ROD	MAX. STROKE	SCREW TYPE	TPI	LEAD ACCURACY†	BACKLASH	MAX THRUST*	DYNAMIC LOAD RATING**	BASE ACTUATOR INERTIA			INERTIA PER/in OF STROKE	DYNAMIC FRICTION TORQUE	MOVING PARTS WEIGHT	
										In Line	Reverse Parallel				Base	Per Inch
											1:1	2:1				
		in	in		turns/in	in/ft	in	lbf	lbf	lb-in ²	lb-in ²	lb-in ²	lb-in ²	lb-in	lb	lb
24	LINEAR	STANDARD Ø0.75	30	SN02	2	0.005	0.007	200	NA	0.116	0.117	0.071	0.005	1.875	4.49	0.33
			30	SN04	4	0.010	0.007	200	NA	0.116	0.117	0.071	0.004	1.125	4.49	0.33
			30	SN08	8	0.010	0.007	200	NA	0.116	0.117	0.071	0.004	1.563	4.49	0.33
			30	BZ10	10	0.006	0.008	850	NA	0.116	0.117	0.071	0.004	2.000	4.49	0.33
			30	BN(L)05	5	0.003	0.015	825	1,411	0.116	0.117	0.071	0.004	1.563	4.75	0.33
			30	BN(L)02	2	0.003	0.015	850	1,071	0.116	0.117	0.071	0.003	1.56	4.75	0.33
	COMPOSITE	STANDARD Ø0.75	30	SN02	2	0.005	0.007	200	NA	0.116	0.117	0.071	0.005	3.438	4.49	0.33
			30	SN04	4	0.010	0.007	200	NA	0.116	0.117	0.071	0.004	2.188	4.49	0.33
			30	SN08	8	0.010	0.007	200	NA	0.116	0.117	0.071	0.004	1.563	4.49	0.33
			30	BZ10	10	0.006	0.008	850	NA	0.116	0.117	0.071	0.004	2.000	4.49	0.33
			30	BN(L)05	5	0.003	0.015	825	1,411	0.116	0.117	0.071	0.004	1.563	4.75	0.33
			30	BN(L)02	2	0.003	0.015	850	1,071	0.116	0.117	0.071	0.003	1.56	4.75	0.33
		OVERSIZED Ø1.00	30	SN02	2	0.005	0.007	200	NA	0.116	0.117	0.071	0.005	3.875	6.06	0.53
			30	SN04	4	0.010	0.007	200	NA	0.116	0.117	0.071	0.004	2.813	6.06	0.53
			30	SN08	8	0.010	0.007	200	NA	0.116	0.117	0.071	0.004	1.875	6.06	0.53
			30	BZ10	10	0.006	0.008	850	NA	0.116	0.117	0.071	0.004	2.188	6.06	0.53
			30	BN(L)05	5	0.003	0.015	825	1,411	0.116	0.117	0.071	0.004	1.875	6.32	0.53
			30	BN(L)02	2	0.003	0.015	850	1,071	0.116	0.117	0.071	0.003	1.88	6.32	0.53
32	LINEAR	STANDARD Ø1.00	36	SN01	1	0.005	0.007	188	NA	0.235	0.179	0.147	0.013	4.375	9.03	0.60
			36	SN02	2	0.005	0.007	300	NA	0.235	0.179	0.147	0.010	3.750	9.03	0.60
			36	BZ10	10	0.006	0.008	785	NA	0.235	0.179	0.147	0.009	2.000	9.03	0.60
			36	BN(L)02	2	0.004	0.015	534	3,364	0.235	0.179	0.147	0.010	3.125	9.51	0.60
			36	BN(L)05	5	0.003	0.015	950	1,624	0.235	0.179	0.147	0.009	1.875	9.51	0.60
			36	BNM20	1.27	0.002	0.005	339	2,560	0.235	0.179	0.147	0.011	1.875	9.51	0.60
	COMPOSITE	STANDARD Ø1.00	36	SN01	1	0.005	0.007	188	NA	0.235	0.179	0.147	0.013	8.688	9.03	0.60
			36	SN02	2	0.005	0.007	300	NA	0.235	0.179	0.147	0.010	4.375	9.03	0.60
			36	BZ10	10	0.006	0.008	785	NA	0.235	0.179	0.147	0.009	2.813	9.03	0.60
			36	BN(L)02	2	0.004	0.015	534	3,364	0.235	0.179	0.147	0.010	3.438	9.51	0.60
			36	BN(L)05	5	0.003	0.015	950	1,624	0.235	0.179	0.147	0.009	2.188	9.51	0.60
			36	BNM20	1.27	0.002	0.005	339	2,560	0.235	0.179	0.147	0.011	2.188	9.51	0.60
		OVERSIZED Ø1.25	36	SN01	1	0.005	0.007	188	NA	0.235	0.179	0.147	0.013	10.000	11.40	0.86
			36	SN02	2	0.005	0.007	300	NA	0.235	0.179	0.147	0.010	5.625	11.40	0.86
			36	BZ10	10	0.006	0.008	785	NA	0.235	0.179	0.147	0.009	3.438	11.40	0.86
			36	BN(L)02	2	0.004	0.015	534	3,364	0.235	0.179	0.147	0.010	4.063	11.88	0.86
			36	BN(L)05	5	0.003	0.015	950	1,624	0.235	0.179	0.147	0.009	2.500	11.88	0.86
			36	BNM20	1.27	0.002	0.005	339	2,560	0.235	0.179	0.147	0.011	2.500	11.88	0.86

SCREW CODE	DESCRIPTION
BN	Ball Nut
BNH	Ball Nut H-series
BNL	Low-Backlash Ball Nut
BNM	Ball Nut Metric

SCREW CODE	DESCRIPTION
BZ	Bronze Nut
RN	Roller Nut
SN	Solid Nut



Contact Tolomatic for higher accuracy and lower backlash options.
 † (L) for low backlash ball screws: backlash = 0.0020" (0.05 mm)

* For SN & BZ screws, maximum continuous dynamic thrust subject to Thrust x Velocity limitation.

** For RN, BN & BNL screws, dynamic load rating reflects 90% reliability for 1 million revolutions.

GSA

GSM Guided Electric Rod-Style Actuator

sizeit.tolomatic.com for fast, accurate actuator selection



ACTUATOR SIZING

SIZE: ALL

units: metric**

SPECIFICATIONS

** GSM metric actuators use the same leadscrew as the GSA inch actuators. Threaded mounting and dowel pin holes are metric.

GSM SIZE	BEARING TYPE	GUIDE ROD	MAX. STROKE	SCREW TYPE	LEAD	LEAD ACCURACY	BACKLASH†	MAX THRUST*	DYNAMIC THRUST RATING**	BASE ACTUATOR INERTIA			INERTIA PER/ 25mm OF STROKE	DYNAMIC FRICTION TORQUE	MOVING PARTS WEIGHT	
										In Line	Reverse Parallel				Base	Per Inch
											1:1	2:1				
										kg-m ² x10 ⁻⁶	kg-m ² x10 ⁻⁶	kg-m ² x10 ⁻⁶	kg-m ² x10 ⁻⁶	N-m	Kg	Kg
12	LINEAR	STANDARD Ø12.7	457.2	SN01	25.40	0.25	0.18	311	NA	1.171	1.463	NA	0.585	0.332	0.549	0.063
			457.2	SN02	12.70	0.15	0.18	311	NA	0.585	0.878	NA	0.293	0.169	0.549	0.063
			457.2	SN05	5.08	0.15	0.18	311	NA	0.585	0.585	NA	0.293	0.064	0.549	0.063
			457.2	BZ10	2.54	0.15	0.20	311	NA	0.585	0.585	NA	0.293	0.049	0.549	0.063
			457.2	BN(L)08	3.18	0.08	0.38	578	1,157	0.585	0.585	NA	0.293	0.056	0.585	0.063
	COMPOSITE	STANDARD Ø12.7	457.2	SN01	25.40	0.25	0.18	311	NA	1.171	1.463	NA	0.585	0.636	0.549	0.063
			457.2	SN02	12.70	0.15	0.18	311	NA	0.585	0.878	NA	0.293	0.318	0.549	0.063
			457.2	SN05	5.08	0.15	0.18	311	NA	0.585	0.585	NA	0.293	0.127	0.549	0.063
			457.2	BZ10	2.54	0.15	0.20	311	NA	0.585	0.585	NA	0.293	0.092	0.549	0.063
			457.2	BN(L)08	3.18	0.08	0.38	578	1,157	0.585	0.585	NA	0.293	0.078	0.585	0.063
		OVERSIZED Ø15.9	457.2	SN01	25.40	0.25	0.18	311	NA	1.171	1.463	NA	0.585	0.692	0.707	0.09
			457.2	SN02	12.70	0.15	0.18	311	NA	0.585	0.878	NA	0.293	0.346	0.707	0.09
			457.2	SN05	5.08	0.15	0.18	311	NA	0.585	0.585	NA	0.293	0.141	0.707	0.09
			457.2	BZ10	2.54	0.15	0.20	311	NA	0.585	0.585	NA	0.293	0.106	0.707	0.09
			457.2	BN(L)08	3.18	0.08	0.38	578	1,157	0.585	0.585	NA	0.293	0.085	0.744	0.09
			609.6	SN01	25.40	0.25	0.18	311	NA	1.756	2.048	NA	0.585	0.332	1.10	0.095
			609.6	SN02	12.70	0.15	0.18	311	NA	0.878	0.878	NA	0.293	0.169	1.10	0.095
			609.6	SN05	5.08	0.15	0.18	311	NA	0.585	0.585	NA	0.293	0.064	1.10	0.095
16	LINEAR	STANDARD Ø15.9	609.6	SN01	25.40	0.25	0.18	311	NA	1.756	2.048	NA	0.585	0.692	1.10	0.095
			609.6	SN02	12.70	0.15	0.18	311	NA	0.878	0.878	NA	0.293	0.346	1.10	0.095
			609.6	SN05	5.08	0.15	0.18	311	NA	0.585	0.585	NA	0.293	0.141	1.10	0.095
			609.6	BZ10	2.54	0.15	0.20	311	NA	0.585	0.585	NA	0.293	0.106	1.10	0.095
			609.6	BN(L)08	3.18	0.08	0.38	578	1,157	0.585	0.585	NA	0.293	0.078	1.13	0.095
	COMPOSITE	STANDARD Ø15.9	609.6	SN01	25.40	0.25	0.18	311	NA	1.756	2.048	NA	0.585	0.692	1.10	0.095
			609.6	SN02	12.70	0.15	0.18	311	NA	0.878	0.878	NA	0.293	0.346	1.10	0.095
			609.6	SN05	5.08	0.15	0.18	311	NA	0.585	0.585	NA	0.293	0.141	1.10	0.095
			609.6	BZ10	2.54	0.15	0.20	311	NA	0.585	0.585	NA	0.293	0.106	1.10	0.095
			609.6	BN(L)08	3.18	0.08	0.38	578	1,157	0.585	0.585	NA	0.293	0.078	1.13	0.095
		OVERSIZED Ø19.1	609.6	SN01	25.40	0.25	0.18	311	NA	1.756	2.048	NA	0.585	0.749	1.33	0.132
			609.6	SN02	12.70	0.15	0.18	311	NA	0.878	0.878	NA	0.293	0.374	1.33	0.132
			609.6	SN05	5.08	0.15	0.18	311	NA	0.585	0.585	NA	0.293	0.148	1.33	0.132
			609.6	BZ10	2.54	0.15	0.20	311	NA	0.585	0.585	NA	0.293	0.113	1.33	0.132
			609.6	BN(L)08	3.18	0.08	0.38	578	1,157	0.585	0.585	NA	0.293	0.085	1.37	0.132

SCREW CODE	DESCRIPTION	SCREW CODE	DESCRIPTION
BN	Ball Nut	BZ	Bronze Nut
BNH	Ball Nut H-series	RN	Roller Nut
BNL	Low-Backlash Ball Nut	SN	Solid Nut
BNM	Ball Nut Metric		



Contact Tolomatic for higher accuracy and lower backlash options.
† (L) for low backlash ball screws: backlash = 0.0020" (0.05 mm)

* For SN & BZ screws, maximum continuous dynamic thrust subject to Thrust x Velocity limitation.

** For RN, BN & BNL screws, dynamic load rating reflects 90% reliability for 1 million revolutions.

GSA

GSM Guided Electric Rod-Style Actuator

SIZE: **ALL** units: **metric****

SPECIFICATIONS

** GSM metric actuators use the same leadscrew as the GSA inch actuators. Threaded mounting and dowel pin holes are metric.

GSM SIZE	BEARING TYPE	GUIDE ROD	MAX. STROKE	SCREW TYPE	LEAD	LEAD ACCURACY	BACKLASH†	MAX THRUST*	DYNAMIC THRUST RATING**	BASE ACTUATOR INERTIA			INERTIA PER/ 25mm OF STROKE	DYNAMIC FRICTION TORQUE	MOVING PARTS WEIGHT	
										In Line	Reverse Parallel				Base	Per Inch
											1:1	2:1				
										kg-m ² x10 ⁻⁶	kg-m ² x10 ⁻⁶	kg-m ² x10 ⁻⁶	kg-m ² x10 ⁻⁶	N-m	Kg	Kg
24	LINEAR	STANDARD Ø19.1	762.0	SN02	12.70	0.13	0.18	890	NA	33.946	34.239	20.777	1.463	0.212	2.04	0.15
			762.0	SN04	6.35	0.25	0.18	890	NA	33.946	34.239	20.777	1.171	0.127	2.04	0.15
			762.0	SN08	3.18	0.25	0.18	890	NA	33.946	34.239	20.777	1.171	0.177	2.04	0.15
			762.0	BZ10	2.54	0.15	0.20	3,781	NA	33.946	34.239	20.777	1.171	0.226	2.04	0.15
			762.0	BN(L)05	5.08	0.08	0.38	3,670	6,275	33.946	34.239	20.777	1.171	0.177	2.15	0.15
			762.0	BN(L)02	12.70	0.08	0.38	3,781	4,764	33.946	34.239	20.777	0.878	0.176	2.15	0.15
	COMPOSITE	STANDARD Ø19.1	762.0	SN02	12.70	0.13	0.18	890	NA	33.946	34.239	20.777	1.463	0.388	2.04	0.15
			762.0	SN04	6.35	0.25	0.18	890	NA	33.946	34.239	20.777	1.171	0.247	2.04	0.15
			762.0	SN08	3.18	0.25	0.18	890	NA	33.946	34.239	20.777	1.171	0.177	2.04	0.15
			762.0	BZ10	2.54	0.15	0.20	3,781	NA	33.946	34.239	20.777	1.171	0.226	2.04	0.15
			762.0	BN(L)05	5.08	0.08	0.38	3,670	6,275	33.946	34.239	20.777	1.171	0.177	2.15	0.15
			762.0	BN(L)02	12.70	0.08	0.38	3,781	4,764	33.946	34.239	20.777	0.878	0.176	2.15	0.15
		OVERSIZED Ø25.4	762.0	SN02	12.70	0.13	0.18	890	NA	33.946	34.239	20.777	1.463	0.438	2.75	0.24
			762.0	SN04	6.35	0.25	0.18	890	NA	33.946	34.239	20.777	1.171	0.318	2.75	0.24
			762.0	SN08	3.18	0.25	0.18	890	NA	33.946	34.239	20.777	1.171	0.212	2.75	0.24
			762.0	BZ10	2.54	0.15	0.20	3,781	NA	33.946	34.239	20.777	1.171	0.247	2.75	0.24
			762.0	BN(L)05	5.08	0.08	0.38	3,670	6,275	33.946	34.239	20.777	1.171	0.212	2.87	0.24
			762.0	BN(L)02	12.70	0.08	0.38	3,781	4,764	33.946	34.239	20.777	0.878	0.212	2.87	0.24
32	LINEAR	STANDARD Ø25.4	914.4	SN01	25.40	0.13	0.18	836	NA	68.770	52.382	43.018	3.804	0.494	4.10	0.27
			914.4	SN02	12.70	0.13	0.18	1,334	NA	68.770	52.382	43.018	2.926	0.424	4.10	0.27
			914.4	BZ10	2.54	0.15	0.20	3,492	NA	68.770	52.382	43.018	2.634	0.226	4.10	0.27
			914.4	BN(L)02	12.70	0.10	0.38	2,375	14,964	68.770	52.382	43.018	2.926	0.353	4.31	0.27
			914.4	BN(L)05	5.08	0.08	0.38	4,226	7,226	68.770	52.382	43.018	2.634	0.212	4.31	0.27
			914.4	BNM20	20.00	0.05	0.13	1,508	11,388	68.770	52.382	43.018	3.219	0.212	4.31	0.27
	COMPOSITE	STANDARD Ø25.4	914.4	SN01	25.40	0.13	0.18	836	NA	68.770	52.382	43.018	3.804	0.982	4.10	0.27
			914.4	SN02	12.70	0.13	0.18	1,334	NA	68.770	52.382	43.018	2.926	0.494	4.10	0.27
			914.4	BZ10	2.54	0.15	0.20	3,492	NA	68.770	52.382	43.018	2.634	0.318	4.10	0.27
			914.4	BN(L)02	12.70	0.10	0.38	2,375	14,964	68.770	52.382	43.018	2.926	0.388	4.31	0.27
			914.4	BN(L)05	5.08	0.08	0.38	4,226	7,226	68.770	52.382	43.018	2.634	0.247	4.31	0.27
			914.4	BNM20	20.00	0.05	0.13	1,508	11,388	68.770	52.382	43.018	3.219	0.212	4.31	0.27
		OVERSIZED Ø31.8	914.4	SN01	25.40	0.13	0.18	836	NA	68.770	52.382	43.018	3.804	1.130	5.17	0.39
			914.4	SN02	12.70	0.13	0.18	1,334	NA	68.770	52.382	43.018	2.926	0.636	5.17	0.39
			914.4	BZ10	2.54	0.15	0.20	3,492	NA	68.770	52.382	43.018	2.634	0.388	5.17	0.39
			914.4	BN(L)02	12.70	0.10	0.38	2,375	14,964	68.770	52.382	43.018	2.926	0.459	5.39	0.39
			914.4	BN(L)05	5.08	0.08	0.38	4,226	7,226	68.770	52.382	43.018	2.634	0.282	5.39	0.39
			914.4	BNM20	20.00	0.05	0.13	1,508	11,388	68.770	52.382	43.018	3.219	0.282	5.39	0.39

SCREW CODE	DESCRIPTION	SCREW CODE	DESCRIPTION
BN	Ball Nut	BZ	Bronze Nut
BNH	Ball Nut H-series	RN	Roller Nut
BNL	Low-Backlash Ball Nut	SN	Solid Nut
BNM	Ball Nut Metric		



Contact Tolomatic for higher accuracy and lower backlash options.
† (L) for low backlash ball screws: backlash = 0.0020" (0.05 mm)

* For SN & BZ screws, maximum continuous dynamic thrust subject to Thrust x Velocity limitation.

** For RN, BN & BNL screws, dynamic load rating reflects 90% reliability for 1 million revolutions.

GSA

GSA Guided Electric Rod-Style Actuator


sizeit.tolomatic.com for fast, accurate actuator selection




ACTUATOR SIZING

SIZE: 12,16: CRITICAL SPEED CAPACITIES

PERFORMANCE



SIZE: 24: CRITICAL SPEED CAPACITIES




SCREW CODE	DESCRIPTION	SCREW CODE	DESCRIPTION
BN	Ball Nut	BZ	Bronze Nut
BNH	Ball Nut H-series	RN	Roller Nut
BNL	Low-Backlash Ball Nut	SN	Solid Nut
BNM	Ball Nut Metric		


GSA Guided Electric Rod-Style Actuator

SIZE: 32: **CRITICAL SPEED CAPACITIES**

PERFORMANCE



SIZE: 12,16: **PV LIMITS (Solid Nuts)**



PV LIMITS

PV LIMITS: Any material which carries a sliding load is limited by heat buildup. The factors that affect heat generation rate in an application are the pressure on the nut in pounds per square inch and the surface velocity in feet per minute. The product of these factors provides a measure of the severity of an application.

$$P \times V \leq 0.1$$

$$\left(\frac{\text{Thrust}}{\text{(Max. Thrust Rating)}} \right) \times \left(\frac{\text{Speed}}{\text{(Max. Speed Rating)}} \right) \leq 0.1$$

GSA

GSA Guided Electric Rod-Style Actuator


sizeit.tolomatic.com for fast, accurate actuator selection




ACTUATOR SIZING

SIZE: 24,32 (SN): PV LIMITS (Solid Nuts)

PERFORMANCE



SIZE: 24,32 (BZ): PV LIMITS (Bronze Nuts)



PV LIMITS

PV LIMITS: Any material which carries a sliding load is limited by heat buildup. The factors that affect heat generation rate in an application are the pressure on the nut in pounds per square inch and the surface velocity in feet per minute. The product of these factors provides a measure of the severity of an application.

$$P \times V \leq 0.1$$

$$\left(\frac{\text{Thrust}}{(\text{Max. Thrust Rating})} \right) \times \left(\frac{\text{Speed}}{(\text{Max. Speed Rating})} \right) \leq 0.1$$


SCREW CODE	DESCRIPTION	SCREW CODE	DESCRIPTION
BN	Ball Nut	BZ	Bronze Nut
BNH	Ball Nut H-series	RN	Roller Nut
BNL	Low-Backlash Ball Nut	SN	Solid Nut
BNM	Ball Nut Metric		

GSA Guided Electric Rod-Style Actuator

BALL SCREW LIFE GRAPHS

PERFORMANCE

SIZE: 12, 16, 24, 32



NOTE: The L_{10} expected life of a ball screw linear actuator is expressed as the linear travel distance that 90% of properly maintained ball screw manufactured are expected to meet or exceed. This is not a guarantee and this graph should be used for estimation purposes only.

The underlying formula that defines this value is:

$$L_{10} = \left(\frac{C}{P_e} \right)^3 \cdot \ell =$$

L_{10} Travel life in millions of units (in or mm), where:

C = Dynamic load rating (lbf) or (N)

P_e = Equivalent load (lbf) or (N)

If load is constant across all movements then:

actual load = equivalent load

ℓ = Screw lead (in/rev) (mm/rev)

Use the "Equivalent Load" calculation below, when the load is not constant throughout the entire stroke. In cases where there is only minor variation in loading, use greatest load for life calculations.

$$\text{Where: } P_e = \sqrt[3]{\frac{L_1(P_1)^3 + L_2(P_2)^3 + L_3(P_3)^3 + L_n(P_n)^3}{L}}$$

P_e = Equivalent load (lbf) or (N)

P_n = Each increment at different load (lbf) or (N)


L = Total distanced traveled per cycle (extend + retract stroke)

[$L = L_1 + L_2 + L_3 + L_n$]

L_n = Each increment of stroke at different load (in) or (mm)

SCREW BUCKLING LOAD

SIZE: 12, 16, 24, 32



NOTE: Buckling load limits shown assume perfect alignment. It is recommended to use additional safety margin, particularly in high thrust applications

SCREW CODE	DESCRIPTION	SCREW CODE	DESCRIPTION
BN	Ball Nut	BZ	Bronze Nut
BNH	Ball Nut H-series	RN	Roller Nut
BNL	Low-Backlash Ball Nut	SN	Solid Nut
BNM	Ball Nut Metric		

GSA

GSA Guided Electric Rod-Style Actuator

sizeit.tolomatic.com for fast, accurate actuator selection



ACTUATOR SIZING

SIZE: ALL

SPECIFICATIONS

GSA(M) SIZE			12				16		24		32		
			17 frame		23 frame								
Guide Rod			STD	OVR	STD	OVR	STD	OVR	STD	OVR	STD	OVR	
WEIGHT	BASE MODEL	IN-LINE	lb	3.65	4.44	3.68	4.47	7.25	7.54	16.48	17.35	27.34	28.65
			kg	1.65	2.01	1.67	2.03	3.29	3.42	7.48	7.87	12.40	13.00
		REVERSE PARALLEL	lb	3.92	4.72	4.05	4.85	7.59	7.88	17.09	17.96	28.81	30.12
			kg	1.78	2.14	1.84	2.20	3.44	3.57	7.75	8.15	13.07	13.66
	PER UNIT OF STROKE	lb/in	0.21	0.27	0.21	0.27	0.30	0.38	0.54	0.74	0.93	1.19	
		g/mm	3.75	4.82	3.75	4.82	5.36	6.79	9.64	13.21	16.61	21.25	
MAX. STROKE			in	18				24		30		36	
			mm	457				609		762		914	
TEMP. RANGE*			°F	40 - 130									
			°C	4 - 54									

⚠ * Heat generated by the motor and drive should be taken into consideration as well as linear velocity and work cycle time. For applications that require operation outside of the recommended temperature range, contact Tolomatic.

LARGE FRAME MOTORS AND SMALLER SIZE ACTUATORS: Cantilevered motors need to be supported, if subjected to continuous rapid reversing duty and/or under dynamic conditions.

SIDE LOADING CONSIDERATIONS: Rod screw actuators are designed to push guided and supported loads and are not meant for applications that require substantial side loading. Please contact Tolomatic for details regarding side loading capabilities.


GSA

GSA Guided Electric Rod-Style Actuator



SIZE: 12

PERFORMANCE

MAX. LOAD WEIGHT & GUIDE ROD DEFLECTION



Linear ball bearings are not available with stainless steel guide rod option.



DO NOT EXCEED MAXIMUM LOAD CURVE

Maximum load values are based on 200 million linear inches of travel.

- To obtain most accurate results, stroke length should be adjusted by the distance between the center of mass of the load and tooling plate.

$$X_{adj} = X_s + X_{cm}$$

Then, use X_{adj} instead of X_s on the Maximum Load Weight vs. Stroke Length graph.



- For the off-center loads, calculate adjusted load weight using the following formula:

$$W_{adj} = W (1 + 0.67 Y_{cm})$$

where Y_{cm} is distance between center of mass of off-center load and center of tooling plate.


Then, use W_{adj} instead of W on Maximum Load Weight vs. Stroke Length graph.

- Using your stroke length and load weight, evaluate guide rod deflection. If the intersection point is above the highest curve (.064"), contact Tolomatic for assistance.



- Impact loading is not recommended for GSA/GSM actuators.
- Motor brakes may be required on vertically positioned actuators with plastic (solid) or ball nuts in applications with risk of load backdriving. (Actuators with bronze nuts will not backdrive for loads, thrusts within catalog specifications.)

Contact Tolomatic for assistance.




GSA





SIZE: 16

PERFORMANCE

MAX. LOAD WEIGHT & GUIDE ROD DEFLECTION



Linear ball bearings are not available with stainless steel guide rod option.



DO NOT EXCEED MAXIMUM LOAD CURVE

Maximum load values are based on 200 million linear inches of travel.

- To obtain most accurate results, stroke length should be adjusted by the distance between the center of mass of the load and tooling plate.

$$X_{adj} = X_s + X_{cm}$$

Then, use X_{adj} instead of X_s on the Maximum Load Weight vs. Stroke Length graph.



- For the off-center loads, calculate adjusted load weight using the following formula:

$$W_{adj} = W (1 + 0.53 Y_{cm})$$

where Y_{cm} is distance between center of mass of off-center load and center of tooling plate.

Then, use W_{adj} instead of W on Maximum Load Weight vs. Stroke Length graph.


- Using your stroke length and load weight, evaluate guide rod deflection. If the intersection point is above the highest curve (.064"), contact Tolomatic for assistance.



GSA

- Impact loading is not recommended for GSA/GSM actuators.
- Motor brakes may be required on vertically positioned actuators with plastic (solid) or ball nuts in applications with risk of load backdriving. (Actuators with bronze nuts will not backdrive for loads, thrusts within catalog specifications.)

Contact Tolomatic for assistance.




GSA Guided Electric Rod-Style Actuator



SIZE: 24

PERFORMANCE

MAX. LOAD WEIGHT & GUIDE ROD DEFLECTION



Linear ball bearings are not available with stainless steel guide rod option.



DO NOT EXCEED MAXIMUM LOAD CURVE

Maximum load values are based on 200 million linear inches of travel.

- To obtain most accurate results, stroke length should be adjusted by the distance between the center of mass of the load and tooling plate.

$$X_{adj} = X_s + X_{cm}$$

Then, use X_{adj} instead of X_s on the Maximum Load Weight vs. Stroke Length graph.



- For the off-center loads, calculate adjusted load weight using the following formula:

$$W_{adj} = W (1 + 0.40 Y_{cm})$$

where Y_{cm} is distance between center of mass of off-center load and center of tooling plate.


Then, use W_{adj} instead of W on Maximum Load Weight vs. Stroke Length graph.

- Using your stroke length and load weight, evaluate guide rod deflection. If the intersection point is above the highest curve (.064"), contact Tolomatic for assistance.



- Impact loading is not recommended for GSA/GSM actuators.
- Motor brakes may be required on vertically positioned actuators with plastic (solid) or ball nuts in applications with risk of load backdriving. (Actuators with bronze nuts will not backdrive for loads, thrusts within catalog specifications.)

Contact Tolomatic for assistance.




GSA





SIZE: 32

PERFORMANCE

MAX. LOAD WEIGHT & GUIDE ROD DEFLECTION





Linear ball bearings are not available with stainless steel guide rod option.



DO NOT EXCEED MAXIMUM LOAD

$$CURVEX_{adj} = X_s + X_{cm} X_{adj} X_s W_{adj} = W (1 + 0.30 Y_{cm}) Y_{cm} W_{adj} W$$




GSA



- Impact loading is not recommended for GSA/GSM actuators.
- Motor brakes may be required on vertically positioned actuators with plastic (solid) or ball nuts in applications with risk of load backdriving. (Actuators with bronze nuts will not backdrive for loads, thrusts within catalog specifications.)

Contact Tolomatic for assistance.



GSA Guided Electric Rod-Style Actuator

SIZE: ALL

3D CAD available at www.tolomatic.com
Always use configured CAD solid model
to determine critical dimensions



DIMENSIONS

Size		K	L	M Ø [2x]	N	P	R	S	T Ø [4x]	U	V	W	X Ø [4x]	Y
12	in	4.500	2.000	0.375 \Downarrow 0.50	1.20	0.297	1.25	1.250	1/4-20 \Downarrow 0.50	0.750	1.500	3.406	0.250 \Downarrow 0.38	5.68
	mm	114.30	50.80	10.00 \Downarrow 12.7	30.5	7.54	31.8	31.75	M6x1.0 \Downarrow 12.7	19.05	38.10	86.51	6.00 \Downarrow 9.5	144.1
16	in	5.438	2.500	0.375 \Downarrow 0.50	1.70	0.516	1.75	1.625	1/4-20 \Downarrow 0.50	1.000	1.750	3.969	0.250 \Downarrow 0.38	6.42
	mm	138.13	63.50	10.00 \Downarrow 12.7	43.2	13.11	44.5	41.28	M6x1.0 \Downarrow 12.7	25.40	44.45	100.81	6.00 \Downarrow 9.5	163.1
24	in	7.000	3.000	0.500 \Downarrow 0.50	2.15	0.438	2.25	1.625	5/16-18 \Downarrow 0.63	1.250	2.750	5.125	0.313 \Downarrow 0.50	8.14
	mm	177.80	76.20	12.00 \Downarrow 12.7	54.6	11.13	57.2	41.28	M8x1.25 \Downarrow 16.0	31.75	69.85	130.18	8.00 \Downarrow 9.5	206.6
32	in	9.000	3.500	0.500 \Downarrow 0.50	2.65	0.594	2.75	2.125	3/8-16 \Downarrow 0.75	1.750	2.750	5.812	0.375 \Downarrow 0.50	9.81
	mm	228.60	88.90	12.00 \Downarrow 12.7	67.3	15.09	69.9	53.98	M10x1.5 \Downarrow 19.1	44.45	69.85	147.62	10.00 \Downarrow 12.7	249.0

Size	Motor Frame	AA	BB	CC 1:1	CC 2:1	DD	EE	FF [2x]	GG	HH	JJ	KK ∞	LL ∞	MM ∞
12	17	in	1.34	3.92	2.63	NA	1.13	0.500	8-32 \Downarrow 0.25	1.66	0.72	1.66	1.85	2.26
		mm	34.1	99.5	66.9		28.6	12.70	M4x0.7 \Downarrow 6.3	42.1	18.3	42.0	47.0	57.3
	23	in	1.34	3.92	2.63		1.13	0.500	8-32 \Downarrow 0.25	1.66	0.72	2.00	2.49	2.26
		mm	34.1	99.5	66.9		28.6	12.70	M4x0.7 \Downarrow 6.3	42.1	18.3	50.8	63.2	57.3
16	23	in	1.34	4.04	2.88	1.38	0.500	8-32 \Downarrow 0.25	1.66	0.72	2.25	2.49	2.26	
		mm	34.1	102.7	73.2	35.0	12.70	M4x0.7 \Downarrow 6.3	42.1	18.3	57.2	63.2	57.3	
24	23	in	2.04	5.13	3.78	3.75	2.04	0.787	1/4-20 \Downarrow 0.31	2.28	1.66	1.42	2.35	2.55
		mm	51.8	130.2	96.1	95.3	51.8	20.00	M6x1.0 \Downarrow 8.6	57.9	42.2	36.0	59.7	64.8
	34	in	2.04	6.29	4.20	4.17	2.04	0.787	1/4-20 \Downarrow 0.31	2.87	2.00	1.42	3.75	3.28
		mm	51.8	159.8	106.6	105.9	51.8	20.00	M6x1.0 \Downarrow 8.6	72.8	50.7	36.0	95.3	83.3
32	23	in	2.58	5.89	4.26	4.28	2.58	0.950	5/16-18 \Downarrow 0.50	3.19	2.00	1.79	3.00	2.63
		mm	65.5	149.6	108.3	108.9	65.5	24.13	M8x1.25 \Downarrow 12.7	80.9	50.7	45.4	76.2	66.8
	34	in	2.58	7.52	5.11	5.08	2.58	0.950	5/16-18 \Downarrow 0.50	3.19	2.00	1.79	3.75	2.38
		mm	65.5	190.9	129.9	129.0	65.5	24.13	M8x1.25 \Downarrow 12.7	80.9	50.7	45.4	95.3	60.5



∞ NOTE: YM code may change this dimension. Always use configured CAD to determine critical dimensions




See dimensional drawing on previous page

GSA

CK & CKS STOP COLLARS



Provides a positive stop mechanism when required.



STANDARD GUIDE RODS

Size		A	B Ø
12	in	0.406	1.125
	mm	10.31	28.58
16	in	0.438	1.313
	mm	11.13	33.35
24	in	0.500	1.500
	mm	12.70	38.10
32	in	0.500	1.750
	mm	12.70	44.45

OVERSIZED GUIDE RODS

Size		A	B Ø
12	in	0.438	1.313
	mm	11.13	33.35
16	in	0.500	1.500
	mm	12.70	38.10
24	in	0.500	1.750
	mm	12.70	44.45
32	in	0.500	2.063
	mm	12.70	52.40

RSA & GSA Electric Rod-Style Actuators

SWITCHES



RSA & GSA products offer a wide range of sensing choices. There are 12 switch choices: reed, solid state PNP (sourcing) or solid state NPN (sinking); in normally open or normally closed; with flying leads or quick-disconnect.

Commonly used for end-of-stroke positioning, these switches allow installation anywhere along the entire actuator length. The internal magnet is a standard feature. Switches can be installed in the field at any time.

Switches are used to send digital signals to PLC (programmable logic controller), TTL, CMOS circuit or other controller device. Switches contain reverse polarity protection. Solid state QD cables are shielded; shield should be terminated at flying lead end.

All switches are CE rated and are RoHS compliant. Switches feature bright red or yellow LED signal indicators; solid state switches also have green LED power indicators.



	Order Code	Lead	Switching Logic	Power LED	Signal LED	Operating Voltage	**Power Rating (Watts)	Switching Current (mA max.)	Current Consumption	Voltage Drop	Leakage Current	Temp. Range	Shock / Vibration
REED	R Y	5m	SPST Normally Open	—	Red	5 - 240 AC/DC	**10.0	100mA	—	3.0 V max.	—	14 to 158°F [-10 to 70°C]	50 G / 9 G
	R K	QD*											
	N Y	5m	SPST Normally Closed	—	Yellow	5 - 110 AC/DC							
	N K	QD*											
SOLID STATE	T Y	5m	PNP (Sourcing) Normally Open	Green	Yellow	10 - 30 VDC	**3.0	100mA	20 mA @ 24V	2.0 V max.	0.05 mA max.		
	T K	QD*											
	K Y	5m	NPN (Sinking) Normally Open	Green	Red								
	K K	QD*											
	P Y	5m	PNP (Sourcing) Normally Closed	Green	Yellow								
	P K	QD*											
	H Y	5m	NPN (Sinking) Normally Closed	Green	Red								
	H K	QD*											

*QD = Quick-disconnect Enclosure classification IEC 529 IP67 (NEMA 6) CABLES: Robotic grade, oil resistant polyurethane jacket, PVC insulation

⚠️ **WARNING: Do not exceed power rating (Watt = Voltage x Amperage). Permanent damage to sensor will occur.

SWITCH INSTALLATION



Place switch bracket into one of the four slots that run the length of the extruded tube. Note that there is a cutout on the actuator head (RSA) or tube (GSA) to allow insertion of the bracket. Insert the switch with the word "Tolomatic" facing up and slide it under the bracket. Position the bracket with the switch to the exact location desired, then lock them securely into place by tightening both set screws on the bracket.

RSA
ST









RSA
HT

GSA

RSA & GSA Electric Rod-Style Actuators

SWITCHES


WIRING DIAGRAMS




SWITCH DIMENSIONS

- direct connect

DETECTION POINT SOLID STATE DETECTION POINT REED





MOUNTING DIMENSIONS



RSA
HT

GSA

- QD (Quick-disconnect) switch



Size	A		B	
	in	mm	in	mm
12	0.68	17.2	0.13	3.3
16	0.77	19.6	0.11	2.9
24	1.06	26.9	0.06	1.5
32	1.31	33.2		
50	1.87	47.5		
64	2.31	58.6		

Dimensions shown in inches [dimensions in brackets millimeters]

APPLICATION DATA WORKSHEET

Fill in known data. Not all information is required for all applications


ORIENTATION

RSA

Horizontal




Incline °




GSA


Horizontal




Horizontal Side



Vertical



Incline °



Load supported by actuator OR Load supported by other mechanism

MOVE PROFILE

EXTEND

Move Distance _____

inch (US Standard) millimeters (Metric)

Move Time _____ sec

Max. Speed _____

in/sec mm/sec

Dwell Time After Move _____ sec

RETRACT

Move Distance _____

inch millimeters

Move Time _____ sec

Max. Speed _____

in/sec mm/sec

Dwell Time After Move _____ sec

NO. OF CYCLES

per minute per hour

HOLD POSITION? Required

Not Required

After Move During Power Loss

NOTE: If load or force changes during cycle use the highest numbers for calculations

EXTEND

LOAD

lb. (U.S. Standard) kg. (Metric)

FORCE

lb. (U.S. Standard) kg. (Metric)

RETRACT

LOAD

lb. (U.S. Standard) kg. (Metric)

FORCE

lb. (U.S. Standard) kg. (Metric)

STROKE LENGTH

inch (US Standard) millimeters (Metric)

DISTANCE FROM TOOLING PLATE TO LOAD CENTER OF GRAVITY*

inch millimeters

NOTE: Use for GSA only, RSA requires external support and guidance for load

PRECISION

Repeatability _____
 inch millimeters

OPERATING ENVIRONMENT


Temperature, Contamination, Water, etc.



FREE: On-line sizing and selection at sizeit.tolomatic.com

Or Call 1-800-328-2174 for Excellent Customer Service & Technical Support

MOTION PROFILE



Graph your most demanding cycle, including accel/decel, velocity and dwell times. You may also want to indicate load variations and I/O changes during the cycle. Label axes with proper scale and units.

CONTACT INFORMATION

Name, Phone, Email
Co. Name, Etc.



USE THE TOLOMATIC SIZING AND SELECTION SOFTWARE AVAILABLE ON-LINE AT www.tolomatic.com OR... CALL TOLOMATIC AT 1-800-328-2174. We will provide any assistance needed to determine the proper actuator for the job.

FAX 1-763-478-8080

EMAIL help@tolomatic.com

RSA
ST

RSA
HT

GSA

RSA & GSA Electric Rod-Style Actuators

Selection Guidelines

1 ESTABLISH MOTION PROFILE

Using the application stroke length, desired cycle time, loads and forces, establish the motion profile details including linear velocity and thrust in each of its segments.

2 SELECT ACTUATOR TYPE

If side (radial) loads are present, select GSA.

3 SELECT ACTUATOR SIZE AND SCREW TYPE

Based on the required velocities and thrust select an actuator size and type and lead of screw drive.

4 VERIFY CRITICAL SPEED OF THE SCREW

Verify that the application's peak linear velocity does not exceed the critical speed value for the size and lead of the screw selected.

5 VERIFY AXIAL BUCKLING STRENGTH OF THE SCREW

Verify that the peak thrust does not exceed the critical buckling force for the size of the screw selected.

6 COMPARE APPLICATION'S PEAK PARAMETERS TO PEAK CAPACITY (PEAK REGION) OF SELECTED ACTUATOR (ROLLER SCREW)

When a roller screw is selected, calculate the application's required peak thrust and peak velocity and compare to the graphs. The selection must satisfy the application's peak requirements.

7 COMPARE APPLICATION'S CONTINUOUS OPERATION PARAMETERS TO CONTINUOUS OPERATION CAPACITY (CONTINUOUS DUTY REGION) OF SELECTED ACTUATOR (ROLLER SCREW)

When a roller screw is selected, calculate the application's continuous operation thrust and velocity and compare to the graph. The selection must satisfy the application's peak requirements.

8 CALCULATE LUBRICATION INTERVAL (ROLLER SCREW)

When a roller screw is selected, calculate the recommended lubrication interval. See page R/GSA_33 and parts sheets for complete lubrication information for the RSA24, RSA32, RSA50 and RSA64.

9 TEMPERATURE CONSIDERATIONS

If the application's ambient temperature lies outside of the allowed range [roller screw: 50° to 122°F (10° to 50°C), all others 40° to 130°F (4° to 54°C), contact the factory. Note that in aggressive applications where roller screw is used, outside temperature of the actuator's body can approach 180°F (82°C), and adequate clearance to avoid overheating of other system components should be allowed.

10 ESTABLISH TOTAL TORQUE REQUIREMENTS

Calculate total system inertia, the peak and the RMS torque required from the motor to overcome internal friction, external forces and accelerate/decelerate the load.

11 SELECT A MOTOR AND A CONTROLLER

Use the obtained total torque value to select a motor and a reduction device (if required). Verify that the peak torque value is below the motor's peak torque curve, and that the continuous torque value is below the motor's continuous torque curve. Verify the minimum torque margin (15%). Verify the inertia match. Select a controller.

12 SELECT A MOTOR-ACTUATOR CONFIGURATION AND SENSORS IF REQUIRED

Select an inline or a reverse-parallel motor configuration. Select mounting and rod end options. Select position sensors (if required). 12 sensor choices include: reed, solid state PNP or NPN, all in normally open or normally closed, with flying leads or quick-disconnect couplers.

13 SELECT ROD END OPTIONS AND MOUNTING OPTIONS

Rod end options include: CLV clevis rod end, SRE spherical rod end, MET externally threaded rod end, ALC alignment coupler, XR rod extension. Mounting options include: TRN trunnion mount, FFG front flange mount, MP2 mounting plates, FM2 foot mount, PCD clevis mount, PCS eye mount, BFG back flange mount.



The above guidelines are for reference only. Use Tolomatic online sizing software for best results.



FREE:
On-line
sizing and
selection at
sizeit.tolomatic.com

ACTUATOR SIZING

Or Call 1-800-328-2174 for
Excellent Customer Service
& Technical Support

RSA & GSA Electric Rod-Style Actuators

SERVICE PARTS ORDERING

RSA ACTUATOR MOUNTING REPLACEMENT KITS

Code	Size	12		16		24		32		50		64ST		64HT	
		Description	RSA	RSM	RSA	RSM	RSA	RSM	RSA	RSM	RSA	RSM	RSA	RSM	RSA
For all motor mounts															
FFG	Front Flange Mount	1107-9013	2107-9013	1112-9013	2112-9013	1124-9022	2124-9032	1132-9022	2132-9042	1150-9022	2150-9042	1164-9022	2164-9022	1164-9384	2164-9384
MP2	Mounting Plate	1107-9015	2107-9015	1112-9014	2112-9014	1124-9023	2124-9033	1132-9023	2132-9043	1150-9023	2150-9043	1164-9023	2164-9023	1164-9375	2164-9375
		1112-9014*	2112-9014*	*Mounting Plate with 23 frame motor or YMH Option (for RSA12 size only)											
For RP motor mounting only															
FM2	Foot Mount	1107-9010	2107-9009	1112-9010	2112-9010	1124-9020	2124-9030	1132-9020	2132-9040	1150-9020	2150-9040	1164-9020	2164-9020	NA	NA
BFG	Back Flange Mount	1107-9014	2107-9014	1112-9013	2112-9025	1124-9022	2124-9032	1132-9022	2132-9042	1150-9022	2150-9042	1164-9022	2164-9022	1164-9384	2164-9384
PCS	Eye Mount	1107-9016	2107-9016	1107-9016	2107-9016	1124-9024	2124-9034	1132-9024	2132-9044	1150-9024	2150-9044	1164-9024	2164-9024	1164-9344	2164-9344
PCD	Clevis Mount	1107-9017	2107-9017	1107-9017	2107-9017	1124-9025	2124-9035	1132-9025	2132-9045	1150-9025	2150-9045	1164-9025	2164-9025	1164-9345	2164-9345

⊗ FM2 Not available with HT option

RSA ROD END REPLACEMENT KITS

Code	Size	12		16		24		32		50		64ST		64HT	
		Description	RSA	RSM	RSA	RSM	RSA	RSM	RSA	RSM	RSA	RSM	RSA	RSM	RSA
CLV	Clevis End	1107-9021	2107-9021	1112-9020	2112-9020	1124-9029	2124-9039	1124-9029	2132-9049	1150-9029	2150-9049	1150-9029	2164-9029	1164-9386	2164-9386
SRE	Spherical Rod Eye	1107-9020	2107-9020	1112-9019	2112-9019	1124-9028	2124-9038	1124-9028	2132-9048	1150-9028	2150-9048	1150-9028	2164-9028	1164-9028	2164-9387
MET	External Threaded	1107-1073	2107-1073	1112-1058	2112-1058	1124-1057	2124-1067	1124-1057	2132-1057	1150-1057	2150-1057	1150-1057	2164-1057	1164-1035	2164-1546
ALC*	Alignment Coupler	1107-1076	NA	1112-1065	NA	1124-9004	2124-1070	1124-9004	2132-1060	1150-9009	2150-1060	1150-9009	2164-1060	1164-9385	2164-1060

ⓘ *NOTE: Alignment coupler is internally threaded, if external thread is desired order MET also

NA = Not Available

GSA OPTIONS REPLACEMENT KITS

Description	SIZE			
	12	16	24	32
Stop Collar	2312-1005	2317-1005	2334-1005	2332-1005
Stainless Steel Stop Collar	2312-1056	2317-1056	2324-1056	2332-1056

Description	SIZE			
	12	16	24	32
Over-Sized Stop Collar	2317-1005	2324-1005	2332-1005	2348-1005
Stainless Steel Over-Sized Stop Collar	2317-1056	2324-1056	2332-1056	2348-1056

ⓘ Kits include one collar and required fasteners

RSA & GSA SWITCHES

To order switch kit use configuration code for switch preceded by SW and actuator code.

EXAMPLE: **SWR** **SA** **24** **KK**

KIT
ACTUATOR
SIZE
SWITCH CODE

The example is for Solid State NPN, Normally Open Switch with Quick-disconnect couplers. Each switch kit is complete with Bracket, Set Screw, Switch and mating QD cable. Note that the bracket/switch size is common and may be used on any size RSA.

To order switch ONLY see part number in table at right

⚠ NOTE: Refer to parts sheets to replace switches on actuators manufactured before 5-10-2010.

Code	Switch & Bracket Part No.	**Switch ONLY Part No.	Lead	Normally	Sensor Type
R Y	8100-9282	8100-9082	5m (197 in)	Open	Reed
R K	8100-9283*	8100-9083*	Quick-disconnect		
N Y	8100-9284	8100-9084	5m (197 in)	Closed	Reed
N K	8100-9285*	8100-9085*	Quick-disconnect		
T Y	8100-9288	8100-9088	5m (197 in)	Open	Solid State PNP
T K	8100-9289*	8100-9089*	Quick-disconnect		
K Y	8100-9290	8100-9090	5m (197 in)	Open	Solid State NPN
K K	8100-9291*	8100-9091*	Quick-disconnect		
P Y	8100-9292	8100-9092	5m (197 in)	Closed	Solid State PNP
P K	8100-9293*	8100-9093*	Quick-disconnect		
H Y	8100-9294	8100-9094	5m (197 in)	Closed	Solid State NPN
H K	8100-9295*	8100-9095*	Quick-disconnect		

**Also order bracket with set screw #1124-9007

*Also order mating QD cable #8100-9080

RSA
ST

RSA
HT

GSA

RSA ST & HT Electric Rod-Style Actuator

ORDERING

ACTUATOR RSA 50 B N 0 2 S K 3 5 R P 1 S T 1 F F G X R 6 **OPTIONS** A L C M E T K K 2 Y M _ _

MODEL & MOUNTING

RSA Rod-Style Screw-Drive Actuator, inch mounting
RSM metric mounting

SIZE

12, 16, 24, 32, 50, 64

NUT/SCREW

SIZE	CODE	TURNS/in (TPI)
12	SN	01,02,05
	BZ	10
	BN, BNL	08
16	SN	01,02,05
	BZ	10
	BN, BNL	08
24	SN	02,04,08
	BZ	10
	BN, BNL	02,05
	RN	05,10
32	SN	01,02
	BZ	10
	BN, BNL	02,05
	BNM	20
50	SN	04
	BZ	10
	BN, BNL	01,02,04
	BNM	05,10,25
64	SN	05,10
	SN	04
	BZ	10
	BN, BNL	02,04,53
	BNM	05,10,20
	BNH	02
	RN	05,10,20

STROKE LENGTH

SK... Enter desired stroke length in decimal inches

SIZE	MAXIMUM STROKE	
	RSA	
	in	mm
12	12	304.8
16	18	457.2
24	24	609.6
32	36	914.4
50	48	1,219.2
64	60	1,524.0

MOTOR MOUNTING

LMI In-line motor mount
RP1 1:1 ratio, reverse parallel motor mount
RP2 2:1 ratio, reverse parallel motor mount
 ❌ **RP2** not available on 12 or 16 size

STANDARD OR HIGH TORQUE

ST1 Standard RS Actuator
HT* High Torque Option
 *requires keyed motor
 ❌ **HT** not available on 12 or 16 size
 NOTE: RN always requires HT option

TRUNNION MOUNT

TRR Trunnion mount
 ❌ Not available on 12 or 16 size with LMI motor mount
 NOTE: Trunnion mount is not available for field retrofit, contact Tolomatic for details

IP67 (RSA32, 50, 64 ONLY)

IP67 Basic ingress protection
 NOTE: *HT actuator (LMI & RP); ST actuator (RP motor mount only)

ACTUATOR MOUNTING

For all motor mounts:
FFG Front Flange Mount
MP2 Mounting Plates (2 required)
 For RP motor mounting only:
FM2* Foot Mount (2 required)
PCD Clevis Mount
PCS Eye Mount
BFG Back Flange Mount
 ❌ *FM2 not available with HT option

Not all codes listed are compatible with all options. Contact Tolomatic with any questions.

ROD EXTENSION

XR... Enter desired rod extension in decimal inches
 ⚠ For vertical applications only.
 NOTE: The XR extension + stroke should not exceed the max. stroke of the specified actuator. (See MAX. STROKE table) Consult Tolomatic for extensions greater than the max. stroke length.

ROD END

Internally threaded rod end is standard
CLV Clevis Rod End
SRE Spherical Rod End
MET Externally Threaded Rod End
ALC Alignment Coupler Rod End*
 *NOTE: Alignment coupler is internally threaded, if external thread is desired order MET also

SWITCHES

TYPE	LOGIC	NORMALLY	QUICK-DISCONNECT	CODE	QUANTITY	LEAD LENGTH
REED	SPST	Open	no	RY	After code enter quantity desired	5 meters (16.4 feet)
		Open	yes	RK		
SOLID STATE	PNP	Open	no	TY		
		Open	yes	TK		
SOLID STATE	NPN	Open	no	KY		
		Open	yes	KK		
SOLID STATE	PNP	Closed	no	PY		
		Closed	yes	PK		
SOLID STATE	NPN	Closed	no	HY		
		Closed	yes	HK		

YOUR MOTOR HERE

YM... Motor mount for non-Tolomatic motor.
www.tolomatic.com



GSA Guided Electric Rod-Style Actuator

ORDERING

ACTUATOR GSA 24 BN02 SK23 RPI **OPTIONS** CBSO CKS KK2 YM

MODEL & MOUNTING	
GSA	Guided Screw-Drive Actuator, inch mounting
GSM	metric mounting

SIZE
12, 16, 24, 32

NUT/SCREW COMBINATIONS		
SIZE	CODE	TURNS/in (TPI)
12	SN	01,02,05
	BZ	10
	BN, BNL	08
16	SN	01,02,05
	BZ	10
	BN, BNL	08
24	SN	02,04,08
	BZ	10
	BN, BNL	02,05
32	SN	01,02
	BZ	10
	BN, BNL	02,05
	BNM	20

STROKE LENGTH		
SK ___	Enter desired stroke length in decimal inches	
MAXIMUM STROKE		
	GSA	
SIZE	in	mm
12	18	457.2
16	24	609.6
24	30	762.0
32	36	914.4

MOTOR MOUNTING	
LMI	In-line motor mount
RP1	1:1 ratio, reverse parallel motor mount
RP2	2:1 ratio, reverse parallel motor mount
✗ <i>RP2 not available on 12 or 16 size</i>	

BEARINGS & GUIDE RODS (GSA ONLY)	
LB	Linear Bearings*
CB	Composite Bearings, Standard Size Rods
COB	Composite Bearings, Over Sized Rods
CBS	Composite Bearings, Standard Size Stainless Steel Rods
CBSO	Composite Bearings, Over-Sized Stainless Steel Rods
✗ <i>*Stainless steel guide rods not available with Linear Bearings</i>	

STOP COLLAR (GSA ONLY)	
CK	Steel Stop Collar
CKS	Stainless Steel Stop Collar
NOTE: The correct Stop Collar will be automatically chosen based on the bearing and guide rod previously selected.	

Not all codes listed are compatible with all options. Contact Tolomatic with any questions.

SWITCHES						
TYPE	LOGIC	NORMALLY	QUICK-DISCONNECT	CODE	QUANTITY	LEAD LENGTH
REED	SPST	Open	no	RY	After code enter quantity desired	5 meters (16.4 feet)
		yes	yes	RK		
Closed	no	yes	NY			
	yes	yes	NK			
SOLID STATE	PNP	Open	no	TY		
		yes	yes	TK		
	NPN	Open	no	KY		
		yes	yes	KK		
PNP	Closed	no	yes	PY		
		yes	yes	PK		
NPN	Closed	no	yes	HY		
		yes	yes	HK		

YOUR MOTOR HERE	
YM _____	Motor mount for non-Tolomatic motor. www.tolomatic.com

GSA



The Tolomatic Difference Expect More From the Industry Leader:



INNOVATIVE PRODUCTS

Tolomatic designs and builds the best standard products, modified products & unique custom products for your challenging applications.



FAST DELIVERY

The fastest delivery of catalog products... Electric products are built-to-order in 15 days; Pneumatic & Power Transmission products in 5 days.



ACTUATOR SIZING

Online sizing that is easy to use, accurate and always up-to-date. Find a Tolomatic electric actuator to meet your requirements.



YOUR MOTOR HERE

Match your motor with compatible mounting plates that ship with any Tolomatic electric actuator.



LIBRARY

Easy to access CAD files available in the most popular formats to place directly into your assembly.



SUPERIOR SERVICE

Our people make the difference! Expect prompt, courteous replies to all of your application and product questions.

Also Consider These Other Tolomatic Products:

Electric Products

Rod & Guided Rod Style Actuators, High Thrust Actuators, Screw & Belt Drive Rodless Actuators, Motors, Drives and Controllers

"Foldout" Brochure #9900-9074



Pneumatic Products

Rodless Cylinders: Band Cylinders, Cable Cylinders, Magnetically Coupled Cylinders/Slides; Guided Rod Cylinder Slides

"Foldout" Brochure #9900-9075



Power Transmission Products

Gearboxes: Float-A-Shaft®, Slide-Rite®, Disc Cone Clutch; Caliper Disc Brakes

"Foldout" Brochure #9900-9076



3800 County Road 116 • Hamel, MN 55340, USA
Phone: (763) 478-8000 • **Fax:** (763) 478-8080
 Toll-Free: **1-800-328-2174**
 sales@tolomatic.com • www.tolomatic.com

EUROPEAN OFFICE

Tolomatic Europe GmbH
 Herriotstraße 1
 60528 Frankfurt am Main
 Germany
Phone: +49 69-6773-3143
 EuropeSales@tolomatic.com

CHINA FACILITY

Tolomatic Automation Products (Suzhou) Co. Ltd.
(ServoWeld® inquiries only)
 No. 60 Chuangye Street, Building 2
 Huqiu District, SND Suzhou
 Jiangsu 215011 - P.R. China
Phone: +86 (512) 6750-8506
Fax: +86 (512) 6750-8507
 ServoWeldChina@tolomatic.com

All brand and product names are trademarks or registered trademarks of their respective owners. Information in this document is believed accurate at time of printing. However, Tolomatic assumes no responsibility for its use or for any errors that may appear in



this document. Tolomatic reserves the right to change the design or operation of the equipment described herein and any associated motion products without notice. Information in this document is subject to change without notice.

Visit www.tolomatic.com for the most up-to-date technical information